

## **PEX clips**

Submittal information

Date submitted:

Project Information	
Job name :	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative :	Approved by :

## Technical Data

Material Plastic

## Product information and application use

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
1" PEX Clip, 50/pkg.	F7051001	-	-	-	0.03
1/2" PEX Clip, 100/pkg.	F7051258	1.685	1.128	0.698	0.016
3/4" PEX Clip, 100/pkg.	F7057500	-	-	-	0.018
3/8" PEX Clip, 100/pkg.	F7060375	1.601	1.128	0.695	0.015

Installation Related applications

Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.

Radiant Heating and Cooling Systems

Codes	Standards	Listings
-	-	-

Trademark Information	Contact information		
	Uponor Inc.	Uponor Ltd.	
ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.	5925 148th Street West	6510 Kennedy Road	
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.636.9517	