

PRO-FLO™

By Tomlinson®

The Pro-Flo™ product line consists of high-quality, lead-free brass and stainless steel water dispensing components for the OEM market. These include bubblers, projector heads, self-contained cartridges, cartridge regulators/holders, fountain glass fillers and point-of-use faucets used by water cooler and drinking fountain manufacturers around the world. These products are NSF listed to ANSI/NSF Std. 61.

Replacement parts for these products are sold separately. See price list for parts.



Bubblers

Lead-free bubblers with easily replaceable self-contained 7701PFLF cartridge regulator. Has 3/8" NPS female connection. Threaded studs and mounting hardware available. Adjustable controlled stream meets conservation criteria. Available with set screw for protection from vandals. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016448	7800PFLF Bubbler, stainless steel
1016128	7800PFLFB Bubbler, lead-free brass
1016452	7800PFLFS Bubbler, stainless steel satin finish
1020888	7800PFLFBFG Bubbler, lead-free brass with flexible antimicrobial guard

NEW



Projector Heads

Chrome plated, lead-free projector heads with removable spout, stream director and screen. Has 3/8" NPS female connection. Available with set screw for protection from vandals. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016170	7-312LFB Projector Head, lead-free brass
1016454	7-312LFB S Projector Head, lead-free brass with set screw



Cartridge

Allows trajectory adjustment over wide range of pressures. Fits all brands of coolers. Stainless steel housing with plastic cover and rubber gasket included. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016337	7701PFSBLF Cartridge, stainless steel with brass cover
1017157	7701PFLF Cartridge, stainless steel with label
1416355	7701PBW Cartridge for cooler, no spring, stainless



Cartridge Holder/Regulator

Has 1/4" NPT female connection. Contains 7701PFLF cartridge. Also available with 5/16" diameter connections for brazing. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016172	7-927LFB Cartridge Holder/Regulator, lead-free brass, solder in
1016171	7-925LFB Cartridge Holder/Regulator, lead-free brass, threaded with 1/4" NPT female threads



Point-of-Use Lead-Free Faucets PF500

The PF500 Series faucets are constructed of highly-polished, chrome plated lead-free brass with preinstalled 1/4" O.D. plastic tubing. The faucet spout is stainless steel. Faucets are available with or without an air gap. Each faucet has a self-closing handle and faucets are individually poly-bagged with mounting hardware. Air gap version has connections for 1/4" inlet and 3/8" outlet. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1420454	PF500LFBR Faucet
1420456	PF500LFBRAG Faucet, with air gap



Fountain Glass Fillers

Fountain glass fillers are constructed of lead-free brass, are lever actuated and have a 3/8" NPS connection. Available with 5" or 8" spout and handle options. Lever actuated vertical mount glass filler is also available with 3/8" NPS female connection. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016166	P200-2LF Glass Filler, 5" spout
1016165	P200-1LF Glass Filler, 8" spout
1016174	V216 Glass Filler, cup trip, vertical mount
1016701	7-906-1 Glass Filler, 3/8" NPS, vertical mount



PRO-FLO™
By Tomlinson®

13700 Broadway Avenue • Cleveland, OH 44125-1992
Phone: 216/587-3400 • FAX: 216/587-6192
www.tomlinsonind.com • World Class, Worldwide

PRO-FLO™

By Tomlinson®

The Pro-Flo™ product line consists of high-quality, lead-free brass and stainless steel water dispensing components for the OEM market. These include bubblers, projector heads, self-contained cartridges, cartridge regulators/holders, fountain glass fillers, point-of-use faucets and freeze prevention bleed valves used by water cooler and drinking fountain manufacturers around the world. Products with NSF listings are listed to ANSI/NSF Std. 61-1999a. *Replacement parts for these products are sold separately. See price list for parts.*



Bubblers

Lead-free bubblers with easily replaceable self-contained 7701PFLF cartridge regulator. Has 3/8" NPS female connection. Threaded studs and mounting hardware available. Adjustable controlled stream meets conservation criteria. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016448	7800PFLF Bubbler, stainless steel
1016128	7800PFLFB Bubbler, lead-free brass
1016452	7800PFLFS Bubbler, stainless steel satin finish



Projector Heads

Chrome plated, lead-free projector heads with removable spout, stream director and screen. Has 3/8" NPS female connection. Available with set screw for protection from vandals.

Model #	Description
1016170	7-312LFB Projector Head, lead-free brass
1016454	7-312LFB S Projector Head, lead-free brass with set screw



Cartridge

Allows trajectory adjustment over wide range of pressures. Fits all brands of coolers. Stainless steel housing with plastic cover and rubber gasket included. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016337	7701PFSBLF Cartridge, stainless steel with brass cover
1016226	7701PFLF Cartridge, stainless steel with plastic cover
1416355	7701PBW Cartridge for cooler, no spring, stainless



Cartridge Holder/Regulator

Has 1/4" NPT female connection. Contains 7701PFLF cartridge. Also available with 5/16" diameter connections for brazing. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016172	7-927LFB Cartridge Holder/Regulator, lead-free brass, solder in
1016171	7-925LFB Cartridge Holder/Regulator, lead-free brass, threaded with 1/4" NPT female threads



Fountain Glass Fillers

Fountain glass fillers are constructed of lead-free brass, are lever actuated and have a 3/8" NPS connection. Available with 5" or 8" spout and handle options. Lever actuated vertical mount glass filler is also available with 3/8" NPS female connection. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016166	P200-2LF Glass Filler, 5" spout
1016165	P200-1LF Glass Filler, 8" spout
1016167	P200-3LF Glass Filler, long reach spout
1016168	V215-LF Glass Filler, push back
1016174	V216 Glass Filler, cup trip, vertical mount
1016701	7-906-1 Glass Filler, 3/8" NPS, vertical mount



Point-of-Use Lead-Free Faucets— PF125 and PF125AG

The PF125 and PF125AG air-gap faucets are lead-free faucets constructed of stainless steel. Base diameter is 2". Ergometric handle has a light touch for long life and allows for intermittent or constant flow. Gooseneck swivels easily and has stream straightener and protective tip. Mounting hardware is included. Air-gap version has barbed wastewater connections for 1/4" tubing in and 3/8" tubing out. Pressure rating is 120 PSI/8 BAR.

Model #	Description
1016186	PF125 Faucet
1016185	PF125AG Faucet, with air-gap

Faucet finishes available in: polished stainless, polished brass, satin brass, satin, almond, black, parchment, white



Freeze Prevention Bleed Valve— V243T

The V243T freeze prevention bleed valve provides protection for solar devices and systems, industrial processing equipment and other water systems that could be damaged by freezing. Positive protection of the equipment is provided even during electrical power failure. 1/2" PTF SAE threads.

Model #	Description
1016469	V243T Freeze Prevention Valve, double threaded



Specifications



Polished Chrome Satin Nickel Antique Bronze Brushed Stainless



Polished Chrome Satin Nickel White Biscuit Polished Brass Antique Bronze Black Bright Nickel Brushed Stainless

Above finishes available in Hot Only and Hot & Cold Faucets in both Designer and Contemporary styles.

Above finishes available in Cold Only RO Faucets in both Designer and Contemporary styles.

Colors may vary slightly from printed samples. See specifications below for style finishes.

Hot Only Faucets

Designer

Model #	Description
1022304	600PBRH, Polished Chrome
1022318	600PBRH, Satin Nickel
1022319	600PBRH, Antique Bronze
1022324	600PBRH, Brushed Stainless

Contemporary

Model #	Description
1021964	600CBRH, Polished Chrome
1022326	600CBRH, Satin Nickel
1022327	600CBRH, Antique Bronze
1022332	600CBRH, Brushed Stainless

Hot & Cold Faucets

Designer

Model #	Description
1022305	600PBRHC, Polished Chrome
1020899	600PBRHC, Satin Nickel
1020900	600PBRHC, Antique Bronze
1020905	600PBRHC, Brushed Stainless

Contemporary

Model #	Description
1022118	600CBRHC, Polished Chrome
1020890	600CBRHC, Satin Nickel
1020907	600CBRHC, Antique Bronze
1020912	600CBRHC, Brushed Stainless

NOTE: Spout reach is approximately 5" (127 mm). Faucet is 12" high (305 mm). Uses preinstalled 1/4" inlet tubing. Pressure rating: 125 PSI/8.3 BAR. Cold side flow rate: .85 gal/min at 35 PSI/2.32 BAR. Hot side flow rate will vary depending on the instant hot water dispenser. Temperature ratings: 40°F/4°C to 190°F/88°C.

Cold Only RO Faucets

Designer

Model #	Description
1019299	600PBR, Polished Chrome
1019301	600PBR, Satin Nickel
1019303	600PBR, White
1019305	600PBR, Biscuit
1019309	600PBR, Polished Brass
1019311	600PBR, Antique Bronze
1019307	600PBR, Black
1019444	600PBR, Bright Nickel
1020518	600PBR, Brushed Stainless

Contemporary

Model #	Description
1020587	600CBR, Polished Chrome
1020889	600CBR, Satin Nickel
1020893	600CBR, White
1020897	600CBR, Biscuit
1020895	600CBR, Polished Brass
1020891	600CBR, Antique Bronze
1020894	600CBR, Black
1020892	600CBR, Bright Nickel
1020896	600CBR, Brushed Stainless

NOTE: Spout reach is approximately 5" (127 mm). Faucet is 12" high (305 mm). Uses preinstalled 1/4" inlet tubing. Pressure rating: 125 PSI/8.3 BAR. Flow rate: 1.0 gpm at 35 PSI/2.32 BAR. Temperature ratings: 40°F/4°C to 150°F/66°C.



Tomlinson Faucets

Designer and Contemporary Styles

Now Available
Three Ways



A whole new degree
of high-style for the
high-end kitchen.

Our Designer and Contemporary faucets give dealers and distributors tremendous up-sell potential for customers who want gorgeous style in their kitchen. Multiple finishes mean these high-end faucets can match any décor. Plus their lead-free brass construction and self-closing "hot" handles make them as safe as they are sensational.

Hot Only and **Hot & Cold** Faucets

Tomlinson now offers "hot only" and "hot & cold" faucets designed to work with instant hot water dispensers. They can also be adapted for use with RO systems.

Available in both Designer and Contemporary styles, these beautifully crafted faucets give you the flexibility you need for today's upscale kitchens and entertainment areas.

Our protective spout tip design prevents after-drip, while self-closing "hot" handles provide additional safety.

- NSF listed to ANSI NSF Std. 61
- Lever-style handles
- Hot handle is self-closing for added safety
- Four finishes: Polished Chrome, Satin Nickel, Antique Bronze and Brushed Stainless
- Protective spout tip design prevents after-drip
- Internal ceramic disc provides smooth operation
- High reach neck of 12" (305 mm) swivels 360°
- All mounting hardware is included
- Preinstalled tubing for quick connections
- Two-year warranty

Compatible with the following hot water dispensers:

- Waste King® (Anaheim Mfg.)
- Everpure® Everhot EV931840
- HT200 Franke® Little Butler Heating Tank
- Everpure® Commercial Grade Instant Hot CGHE1
- Little Gourmet®
- KitchenAid® (Whirlpool®)
- Mountain Plumbing MT641
- Quick & Hot® Waterstone #5000 Hot Tank
- Solaria™ Instant Hot Water Dispenser EV9318-40

NOTE: Not compatible with InSinkErator products.



Cold Only RO Faucets

Our cold water Designer and Contemporary RO faucets are a cool addition to any kitchen.

Nine fabulous finishes let you match virtually any décor. Plus the lead-free brass construction of the faucets is quality all the way.

Tomlinson's faucets are a real standout – and a great opportunity for you to set yourself apart.

- NSF listed to ANSI NSF Std. 61
- Designs complement today's high-end kitchens
- Nine finishes to match any décor
- Lever-style handles
- Protective spout tip design prevents after-drip
- Internal ceramic disc provides smooth operation
- High reach neck of 12" (305 mm) swivels 360°
- All mounting hardware is included
- Preinstalled tubing for quick connections
- Patented modular air gap (U.S. patent #7,011,106)
- Retrofits most brands
- Two-year warranty

