




30° EII

Socket x Socket




Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
815-005F*	1/2	1- 7/16	7/16	1- 1/8	.08
815-007F*	3/4	1- 7/16	7/16	1- 3/8	.12
815-010F*	1	1- 3/4	1/2	1-11/16	.16
815-012F*	1-1/4	2- 3/16	11/16	2- 1/16	.29
815-015F*	1-1/2	2- 3/16	11/16	2- 5/16	.35
815-020F*	2	2- 1/2	3/4	2-13/16	.57
815-025F*	2-1/2	3	1	3- 7/16	1.05
815-030F*	3	3- 5/16	1- 1/16	4- 1/8	1.46
815-040F*	4	3- 7/16	1- 3/16	5- 3/16	2.13
815-045F*	4-1/2	4	1- 1/2	5- 5/8	2.84
815-050F*	5	4- 3/8	1- 3/8	6- 5/16	3.30
815-060	6	4-13/16	1-13/16	7-5/8	5.59
815-080F*	8	6- 3/16	1-15/16	9- 5/8	10.65
815-100F*	10	7- 3/4	2- 1/2	11-15/16	18.51
815-120F*	12	9- 1/16	2-13/16	14- 1/8	28.97
815-140F*	14	10- 7/16	3- 7/16	15- 1/2	37.94
815-160F*	16	11-15/16	3-15/16	17-11/16	61.48
815-180F*	18	13-1/2	4-1/2	19- 7/8	83.85
815-200F*	20	15	5	22- 1/16	112.87
815-240F*	24	18- 1/8	6- 1/8	26- 7/16	191.00

* Fabricated

22-1/2° EII

Socket x Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
816-005	1/2	1- 1/16	3/16	1- 5/32	.11
816-007	3/4	1- 3/16	7/32	1-13/32	.08
816-010	1	1-11/32	7/32	1-23/32	.26
816-010F*	1	1-11/16	7/16	1-11/16	.16
816-015F*	1-1/2	2- 1/8	5/8	2- 5/16	.29
816-012	1-1/4	1- 1/2	1/4	2- 3/32	.19
816-015	1-1/2	1-21/32	9/32	2-11/32	.25