

## **LEAD FREE\***

# Model 161T-LF **CLASS 125 SWING CHECK**

BRONZE SEAT, NPT

(61YLF SERIES)

Job Name:	Contractor:	
Job Location:	P.O. Number:	
Engineer:	Representative:	
Tag:	Wholesale Distributor:	

### Description

The Lead Free\* Apollo Model 161T-LF (61YLF Series) Swing Check provides a reliable, long lasting, "Made in the USA" alternative to globally sourced check valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials. The Apollo Swing Check may be installed in either horizontal or vertical orientation with upward flow.

#### **Features**

- Lead-Free\* ANSI 3rd Party Certified
- · Dezincification Resistant Bronze Construction
- · Renewable Bronze Seat Disc
- 100% Factory tested per MSS SP-139
- NPT Connections
- · Cast, Machined and Assembled in the USA
- ARRA Compliant

#### Standards

MSS SP-139, "Copper Alloy Gate, Globe, & Check Valves" NSF/ANSI 61-8, Annex F & G ASME B1.20.1, "Pipe Threads, General Purpose (Inch)" CSA B51 CRN 0C14667.5

#### Performance Rating

Cold Working Pressure: 200 psi (13.8 Bar) at 100°F

Temperature Range: -20°F to 406°F

\* LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB1953, VT Act 193, MD HB372, LA HB471 and Federal Public Law

## **Ordering Information**

Size	Model	Item Number	
□ 1/4"	161T14LF	61YLF191-01	
□ 3/8"	161T38LF	61YLF192-01	
☐ ½"	161T12LF 61YLF193-01		
3/4"	161T34LF	61YLF194-01	
□ 1"	161T1LF	61T1LF 61YLF195-01	
☐1-1/4"	1-1/4" 161T114LF 61YLF196-0		
1-½"	161T112LF	61YLF197-01	
□ 2"	161T2LF	61YLF198-01	

Warning: Do not use in reciprocating compressor service.



Material Specifications

material opecifications				
Part Name	Material			
Body	ASTM B584-C89836 Bronze			
Сар	ASTM B584-C89836 Bronze			
Hanger	304 Stainless Steel or ASTM			
	B584 C89836 Bronze			
Pin	304 Stainless Steel			
Seat	UNS 27450 Lead Free* Brass			
Plug	ASTM B16 Brass			

**Physical Specifications** 

<u> </u>	,						
Size	Height	Length	Weight	Cv			
Size	(in.)	(in.)	(lbs)	(gpm)			
1/4"	1.51	2.14	.64	2.6			
3/8"	1.51	2.14	.62	4.5			
1/2"	1.65	2.48	.73	7.0			
3/4"	1.9	2.94	1.1	12.0			
1"	2.26	3.57	1.7	28.6			
1-1/4"	2.99	4.50	3.4	39.0			
1-1/2"	2.99	4.50	3.1	56.0			
2"	3.74	5.25	5.5	152.0			





Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA; www.apollovalves.com; 704-841-6000