



LYON STATION, PA 19536 • Phone: 610-682-6361 • Fax: 610-682-4781  
Order Department Hotline: 610-682-4231  
www.dekabatteries.com

# MARINE MASTER®

GROUP NO.	PART NO.	CCA	REF. MCA	20 HR CAP	MINS @ 23 A	MINS @ 25 A	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
<b>12-VOLT MARINE / RV STARTING CALCIUM MAINTENANCE-FREE</b>																
24	24M7	800	1000	—	—	130	46	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M6	650	800	—	—	115	40	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M5	550	675	—	—	90	37	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M4	460	565	—	—	70	36	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
27	27M6	840	1050	—	—	182	53	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	17,U
<b>12-VOLT MARINE / RV DUAL PURPOSE STARTING / CYCLE SERVICE</b>																
24	DP24	550	675	65	140	120	44	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	12,17,44,U
27	DP27	650	800	80	175	150	51	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	12,17,44,U
31	DP31DT	700	860	100	205	185	57	13	330	6-3/4	171	9-1/2	241	1.5	12	17,21,22,44,A
<b>12-VOLT MARINE / RV DEEP CYCLE SERVICE</b>																
24	DC24	500	615	75	150	130	45.5	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	11,17,35,44,U
27	DC27	575	705	90	200	175	53.5	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	11,17,35,44,U
31	DC31DT	650	800	105	225	190	60	13	330	6-3/4	171	9-1/2	241	1.5	12	11,17,21,22,35,44,A

Note: "DC" (deep cycle) part numbers include double insulated glass mat separators.

## Deka INTIMIDATOR® AGM VALVE-REGULATED ABSORBED GLASS MAT TECHNOLOGY

GROUP NO.	PART NO.	CCA	REF. MCA	R.C.	MINS @ 25 A	20 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
<b>8-VOLT MARINE AND INDUSTRIAL</b>																
983	819	510	625	167	158	119	119	24-1/2	622	7-1/2	191	10-1/2	267	3.0	6	11,17,20,25,35,T
984	821	530	650	187	177	135	821	27-1/2	699	7-1/2	191	10-1/2	267	3.0	6	11,17,20,25,35,T
985	825	730	900	224	212	160	160	26-7/8	683	8-1/2	216	11-3/4	298	4.0	6	11,17,20,25,35,F

## Deka DOMINATOR® GEL VALVE-REGULATED GELLED ELECTROLYTE TECHNOLOGY

GROUP NO.	PART NO.	CCA	REF. MCA	R.C.	MINS @ 25 A	20 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
U1	8AU1	200	240	45	54	32	23	7-3/4	197	5-1/8	130	7-1/4	184	0.5	12	2,38,39,44,Y
	8AU1H	200	240	45	54	32	23	8-5/16	211	5-1/8	130	7-1/4	184	0.5	12	2,17,38,39,44,Y
22NF	8A22NF	350	420	85	95	55	37	9	228	5-1/2	140	9-1/4	235	0.5	12	2,38,39,44,G
24M	8A24M	525	800	135	145	79	52	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,U
24	8A24	525	800	135	145	79	52	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,G
	8A24NH	525	800	135	145	79	52	10-1/4	260	6-3/4	171	9-3/8	238	1.0	12	2,38,39,44,G
27M	8A27M	580	900	175	185	92	61.5	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,U
27	8A27	580	900	175	185	92	61.5	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,G
31M	8A31DTM	800	1000	200	210	105	67.5	12-15/16	329	6-3/4	171	9-3/8	238	1.5	12	2,16,17,38,39,44,A
4D	8A4D	1110	1420	380	413	198	133.5	20-3/4	527	8-1/2	216	10	254	3.0	12	2,17,44
8D	8A8D	1450	1800	480	517	245	163	20-3/4	527	11	279	10	254	4.0	12	2,17,44
GC2 (ev)	8AGC2	680	900	380	409	190	68	10-1/4	260	7-1/8	181	10-7/8	276	1.5	12	2,44,U

- Batteries are maintenance-free calcium grids, except where noted
- Batteries manufactured in polypropylene cases & covers
- Batteries manufactured in black cases & covers, except where noted
- SAE automotive posts used, unless noted
- Warranty is suggested months
- Weights are approximates
- MCA and CA ratings @ 32°F are approximations for comparison only
- Ratings except CCA and RC, are "nominal"
- CCA and RC ratings conform to B.C.I. specifications
- CCA on 8 Volt Marine & Industrial Types is for reference only

MEMBERS OF:



E.P.M. Form No. 0194 © 2019 Rev 10/24/19 by EPM, Printed in U.S.A.  
No Part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.



- A. Flush Combination terminal w/ 5/16" Stud and SAE post, Hex nuts included
- B. Flag Terminal w/ 3/8" diameter hole (T876)
- C. 1/4" 20 Copper insert terminal
- F. Double Wide L Terminal w/ two 3/8" holes (T230)
- G. Offset post w/ horizontal hole, stainless steel 5/16" bolt and hex nut (T881)
- T. Heavy Duty L terminal w/ 3/8" diameter hole (T975)
- U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs and wing nuts
- X. 3/8"-16 stainless steel stud posts
- Y. Small L terminal with round hole (T873)

FOOTNOTES

- Black cover / Gray case
- Gray cover / Gray case
- Low maintenance-low antimony grids
- Hybrid construction
- Dual terminal universal design
- Includes handle
- Hard rubber, multi-cell cover construction
- Anchor locked elements
- Flush manifold vented cover
- With individual vent caps
- Deduct 15% from CCA and CA rating to allow for double insulation (glass mat)
- "Non-spillable" defined by DOT (Department of Transportation) definitions
- "Non-spillable" defined by ICAO (International Civil Aviation Organization) and IATA (International Air Transport Association) definitions
- Free Replacement Warranty is 3 months in full electric vehicle use

**PROPOSITION 65 WARNING:** Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. WASH HANDS AFTER HANDLING.