

# STANDARD FITTINGS

**No. 40 – Grooved x Threaded Adapter Nipple**

**No. 42 – Grooved x Beveled Adapter Nipple**

**No. 43 – Grooved x Grooved Adapter Nipple**

Size		No. 40, 42, 43 Adapter Nipple (s)
Nominal Size inches	Actual Pipe Outside Diameter inches/mm	E to E inches/mm
¾	1.050 26.9	3.00 76
1	1.315 33.7	3.00 76
1¼	1.660 42.4	4.00 102
1½	1.900 48.3	4.00 102
2	2.375 60.3	4.00 102
2½	2.875 73.0	4.00 102
3	3.500 88.9	4.00 102
3½	4.000 101.6	4.00 102
4	4.500 114.3	6.00 152
5	5.563 141.3	6.00 152
6	6.625 168.3	6.00 152
8	8.625 219.1	6.00 152
10	10.750 273.0	8.00 203
12	12.750 323.9	8.00 203



**No. 40**



**No. 42**



**No. 43**

Available with British Standard Pipe Threads. Specify "BSPT" clearly on order.

For pump package nipples with a 1½-inch/38-mm hole cut to receive Style 923 Vic-Let Strapless Outlets or Style 924 Vic-O-Well Strapless Thermometer Outlets, special No. 40, No. 42, or No. 43 Adapter Nipples must be used. Specify No. 40-H, 42-H, or 43-H clearly on order. NOTE: An 8-inch/203-mm minimum length is required for 4 – 12-inch/114.3 – 323.9-mm sizes.

# For use on cut grooved systems only. For roll grooved systems, Victaulic offers the Advanced Groove System (AGS).

**NOTE:** All fittings are ductile iron unless noted otherwise with an "sw" or "s".

SW = Segmentally Welded, S = Carbon Steel



Always refer to the current Victaulic submittal publication in the G-100 General Catalog or on the website [www.victaulic.com](http://www.victaulic.com) for the most up-to-date dimensional information.

