

Industrial Hose, Valves & Process Equipment

3 Way Normally Closed Pilot Operated Valve



Solenoid Enclosure: NEMA 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Brass Body Material

Pipe Size NPT (in)	Orifice Size (in)	Pressure Cv Flow	Exhaust Cv Flow	Operating Pressure Differential (psi)	Max. Air/Inert Gas Pressure Differential (psi)	Max. Water Pressure Differential (psi)	Max. Light Oil Pressure Differential (psi)	Watt Rating (W)	Seal Material	Coil Type	AC Voltage			
											Order No.	Mfr. No.	Model No.	Net Price
3/8	3/8	2.1	2.1	10 to 180	180	180	180	10	Buna-N	Skinner Valve	MA2391911	S0360	73312BN3RNJONONOC111P3	\$284.39
1/2	1/2	3.6	3.6	10 to 180	180	180	180	10	Buna-N	Skinner Valve	MA2393752	S5189	73312BN4UNMJNOC111P3	298.00
3/4	3/4	7.3	7.3	10 to 180	180	180	180	10	Buna-N	Skinner Valve	MA2392010	S0524	73312BN52NJJONOC111P3	376.52

4 Way Single Solenoid Pilot Operated Valve



Applications:

- Air vises
- Air motors
- Dampers
- Pilots

Compliances:

- UL® and CSA approvals are generally available on valves with applicable coil/enclosure combinations

Caution:

- Use of nonlubricated gaseous media will substantially limit valve life
- Valves should be mounted vertical and upright
- Avoid exhaust flow restriction

Solenoid Enclosure: NEMA 4, 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Brass Body Material

Pipe Size NPT (in)	Orifice Size (in)	Cv Flow	Operating Pressure Differential psi	Watt Rating (W)	Seal Material	Coil Type	AC Voltage		
							Order No.	Mfr. No.	Net Price
1/4	3/32	0.09	10 to 150	11	Buna-N	Gold Ring Valve	MA9876793	04F48S2106ACF4C05	\$164.72

General Purpose 4 Way Pilot Operated Solenoid Valve



Applications:

- Air vises
- Air motors
- Dampers
- Pilots

Compliances:

- UL® and CSA approvals are generally available on valves with applicable coil/enclosure combinations

Caution:

- Use of nonlubricated gaseous media will substantially limit valve life
- Valves should be mounted vertical and upright
- Avoid exhaust flow restriction

Solenoid Enclosure: NEMA 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Aluminum Body Material

Pipe Size NPT (in)	Orifice Size (in)	Cv Flow	Watt Rating	Operating Pressure Differential (psi)	Seal Material	Coil Type	Mechanical Options	AC Voltage		
								Order No.	Model No.	Net Price
1/4	1/4	1	10	30 to 150	Buna-N	Skinner Valve	None	MA1870711	73419AN2NNONOC111P3	\$151.68
							Manual Override	MA1870712	73419AN2NNMONOC111P3	174.31

APPLIED® IS WORKING FOR YOU!

“The role we play as a distributor is more important today than ever before. Customers do not keep as much inventory on hand, so they depend on the distributor to get them the correct part fast. If we do this consistently, the customer will trust us with their business. And after being in this business for 40 years, I believe our personal relationship with our customers still means a great deal.”

— Donald Fore, Customer Sales & Service Representative, Albany, GA

