



4700 W. 160th St.
 Cleveland, OH 44135
 PH:800-321-9532
 FX:800-321-9535
 www.oatey.com
 TECHNICAL SPECIFICATION

KNOCK-OUT™ TEST CAPS



TECHNICAL SPECIFICATION: Oatey Knock-Out Test Caps are a solvent weld test cap designed for use on Schedule 40 ABS or PVC DWV piping for testing up to 17 PSI or 40' head pressure. Knock-Out Test Caps deep design provides strong, leak-free connection, while "tab" feature keeps hands free from solvent cement. Knock-Out center of test cap can be removed with "tab" to prevent possible blockage in piping.



PHYSICAL/CHEMICAL PROPERTIES

Material ABS
 Color White

DIRECTIONS FOR USE

Solvent Weld Knock-Out Test Cap into piping end and conduct hydrostatic pressure test up to 17 PSI or 40' head pressure.

PRECAUTIONS

Do not stand in the danger zone while test is in progress.
 Never test piping system using compressed air.

COMMON APPLICATIONS

Oatey Knock-Out Test Caps are a solvent weld test cap designed for testing up to 17 PSI or 40' head pressure.

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33460	1-½" Knock-Out Test Cap Plug	1500	20 lbs.
39100	1-½" Knock-Out Test Cap Plug	20	1 lb.
33461	2" Knock-Out Test Cap Plug	1200	22 lbs.
39101	2" Knock-Out Test Cap Plug	20	1 lb.
33462	3" Knock-Out Test Cap Plug	500	17 lbs.
39102	3" Knock-Out Test Cap Plug	15	2 lbs.
33463	4" Knock-Out Test Cap Plug	300	17 lbs.
39103	4" Knock-Out Test Cap Plug	15	2 lbs.