

For Residential and Light Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

PURE WATER

Model PWDWUFKC3 Kwik-Change™ Ultra Filtration Membrane Water Filtration System

Features

- Equipped with long reach faucet for easy fill
- Kwik-Change™ cartridges are the fastest changeable cartridges on the market (30-second filter changeout process)
- ¼-turn pivot filter head makes for ease of accessibility and filter change, reduces the amount of tube connections for greater reliability and reduces leak potential
- Cartridges connect to and disconnect from the unit by a simple ¼-turn
- Space saving design installs under sink or in limited space
- Double Seal O-ring cartridges ensure system integrity
- No storage tank needed
- Requires only normal line pressure to operate
- Dispenses a continuous supply of water
- Requires minimal maintenance and will provide years of clean, safe, great-tasting water

Reliability and Performance

- Advanced design uses unique technology and high-quality components to ensure years of continuous operation with trouble-free performance
- The Kwik-Change™ System water quality output exceeds the purity of other filtration and faucet mount devices

Performance

Tested	% of Reduction
Cysts	99.95
Cryptosporidium	99.95
Entamoeba	99.95
Giardia	99.95
Toxoplasma	99.95
Chlorine	98.00



System tested and certified by
WQA against NSF/ANSI Standard
372 for "lead free" compliance



PWDWUFKC3

Specifications

Stage 1: Sediment Filter removes particles down to 5 micron

Stage 2: Carbon Block Filter removes objectionable taste, chlorine taste, and odors

Stage 3: UF Membrane consists of a bundle of ultrafiltration membranes that are a physical barrier to particles, suspended solids, turbidity, most colloids, and impurities as small as 0.25 microns

- Adapt-A-Valve™ easily connects to water source
- Automatic shutoff valves in the manifold, therefore, no need to shut off the incoming water supply when changing out the filters
- Proprietary sanitary filter cartridges eliminate water spills during cartridge replacement

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

System Specifications

Temperature: Minimum 40°F (4.4°C),
Maximum 100°F (37.8°C)

Pressure: Minimum 20psi (1.4kg/cm²)
Maximum 85psi (6 kg/cm²)

pH: Minimum 2, Maximum 11

Rated Capacity: 2000 Gal. (7570 liters)

Unit Dimensions: Approx. 10" W x 15" H x 4" D

Replacement Filter Packs

MODEL	FREQUENCY	DESCRIPTION
PWFPK2KC4	6 Months	Includes sediment and carbon pre-filter only
PWFPKCUF	Annual	Includes all filters and UF membrane

Note: Water conditions may require more frequent cartridge replacement



A Watts Water Technologies Company

ES-WQ-PWDWUFKC3 1248



USA: Tel. (800) 224-1299 • www.watts.com
Canada: Tel. (888) 208-8927 • www.watts.ca

© 2012 Watts