



# **Model EXV - LF**Thermal Expansion Relief Valve

(78LF-RV Series)

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

### DESCRIPTION

The Lead Free\* Apollo® 78LF-RV Series Combination Water Heater Isolation Valve/ IAPMO approved Thermal Expansion Relief Device solves two Code requirements while saving time, installation space and money! Ideal alternative to expansion tanks in residential plumbing systems. Made in the USA, featuring Lead Free\* dezincification resistant bronze materials.

## **MATERIAL SPECIFICATIONS**

Part Name	Material
Lever	Steel, Plated, Plastisol
Body	UNS C89836 Lead Free* Bronze
Stem Bearing	RTFE
Stem	UNS C27451 Lead Free* Brass
Retainer	UNS C27451 Lead Free* Brass
Ball	UNS C27451 Lead Free* Brass
Stem Packing	RTFE
Seat	RTFE
Body, Relief	UNS C89836 Lead Free* Bronze
Spring, Relief	Stainless Steel
Seat, Relief	Silicone Rubber

**DIMENSIONS (in.)** 

Size	A(in.)	B(in.)	C(in.)	Port Dia.(in.)
¾" SWT	4.0	3.9	3.3	.687
¾" FNPT	3.9	2.8	3.3	.750
3/4" PEX	3.9	3.8	3.3	.750

PART NUMBER Example: 78LF305RV

TATAL TAGINGE EXAMPLE: TOLI COOKY						
78LF	SIZE/CONN	PRESSURE*	OUTLET + RV			
	<b>3</b> -3/4" SOLDER	<b>0</b> - 125 PSI	4- HOSE			
	<b>4</b> -3/4" THREAD	<b>1</b> - 100 PSI	<b>5</b> - PEX			
	<b>7</b> -3/4" PEX	<b>2</b> - 80 PSI	6- COMPRESS			
			<b>7</b> - ½"SWT/THD			

<sup>\*</sup> Consult factory for pressure settings not listed.

### PERFORMANCE RATING

Ball Valve Maximum Pressure: 400 psi Relief Valve factory set and sealed, 125 psi Maximum Maximum Temperature 210°F



**MODEL EXV** - □ - □ - □ - 34 - LF

Ball Valve Connection:


FNPT (T) Solder (S) Pex (X)


<u>Set Pressure (PSI):</u> 80 □ 100 □ 125 □

Discharge Type:

**HB** ☐ Hose Barb **X** ☐ Pex **C** ☐ Compression

**S** ☐ Sweat / threaded combination





## **APPROVALS**

CSA B125 IAPMO IGC 128-2006a City of Los Angeles NSF/ANSI 61-8, Annex G



NSF 372 LEAD FREE\* ANSI 3RD Party Certified

\* **LEAD FREE**: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB1953, VT Act 193, MD HB372, LA HB471 and Federal Public Law 111-380.

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28106 USA; www.apollovalves.com; 704-841-6000