Technical Specifications

REMWP Outdoor Emergency Remote Heads

RF	MW	/P

Simkar REM Remote Heads whether installed alone or in conjunction with other quality exit and emergency products are an economical way to light the path of egress.

Date





HOUSING Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

ILLUMINATION Smooth thermoplastic reflector with plastic lens for optimal light distribution. Adjustable lamp heads with 6V and 12V wedge base incandescent lamps provides increased center-to-center spacing.

MOUNTING Universal mounting base plate included with mounting hardware. Distance of maximum run is determined

by system voltage, wire gauge and total maximum wattage on the run. Suitable for wall or ceiling mount.

ELECTRICAL Powered from low voltage power source with low voltage wiring (not provided)

OPTIONS Weatherproof (option WP) is available.


LISTINGS ETL listed. Meets UL924, NFPA101 Life Safety Code, and NEC requirements.

WARRANTY 3 year limited warranty.

REMWP Outdoor Emergency Remote Heads Configuration

_ _					
SERIES	HEADS	HOUSING	COLOR	VOLTAGE	WATTAGE
REM	1	WP = Weatherproof (Standard)	Blank = White (Standard)	6 = 6V	5.4 = 5.4 Watts
	2		B = Black	12 = 12V	7.2 = 7.2 Watts
					9.0 = 9.0 Watts
					12.0 = 12.0 Watts

Dimensions



Fixture Compatibility

Series	6V	12V
SHDEM	Х	Х
SWLEM	Х	
SLCLI	Х	

Reference individual unit equipment specification sheets for remote load capacity availability.

