



Schedule 80 PVC Technical Schedule 80 Fittings

Wye - Reducing

(Continued)


Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure

Rating @ 73°F (23°C) 2-1/2" - 6" - 150 psi

Maximum Internal Pressure Rating @ 73°F (23°C)
8" - 10" & All Fabricated Sizes - 100 psi

Maximum Internal Pressure Rating @ 73°F (23°C)
12" 80 psi Maximum Internal Pressure Rating
@ 73°F (23°C)



Part Number	Size	G	G1	G2	H	H1	H2	L	M	M1	Approx. Wt. (Lbs.)
875-291 ¹	2-1/2X1-1/2	27/32	4-23/32	3-31/32	2-19/32	6-1/8	5-23/32	8-5/16	3-1/2	3-1/2	2.37
875-292 ¹	2-1/2X2-1/2X2	27/32	4-1/2	3-31/32	2-19/32	6	5-23/32	8-5/16	3-1/2	3-1/2	2.23
875-335 ¹	3X1	31/32	5-13/16	4-3/4	2-7/8	6-31/32	6-5/8	9-1/2	4- 3/16	4- 3/16	3.58
875-336 ¹	3X1-1/4	31/32	5- 3/4	4-3/4	2-7/8	7-1/32	6-5/8	9-1/2	4- 3/16	4- 3/16	3.62
875-337 ¹	3X1-1/2	31/32	5-3/4	4-3/4	2-7/8	7-1/32	6-5/8	9-1/2	4- 3/16	4- 3/16	3.58
875-338 ¹	3X2	31/32	5-7/16	4- 3/4	2- 7/8	6-31/32	6- 5/8	9- 1/2	4- 3/16	4- 3/16	3.59
875-339 ¹	3X2-1/2	7/8	4- 1/8	4-21/32	2- 3/4	6- 3/4	6	8- 3/4	4- 3/16	4- 3/16	3.36
875-419 ¹	4X1-1/2	1-3/32	5-3/16	4-15/32	2-5/32	6-19/32	4-15/32	8-29/32	5-1/4	2-7/8	3.06
875-420	4X2	3/32	4-7/8	4-15/32	2-5/32	6-3/8	6-3/4	8-29/32	5-1/4	2-7/8	2.92
875-420F ^{2*}	4X2	3-3/4	7-7/8	8-1/4	6	9-5/8	10-1/2	16-1/2	5-3/16	2-13/16	6.92
875-421F ^{2*}	4X2-1/2	1-7/8	8-1/4	6-3/8	4-1/8	10-1/4	8-5/8	12-3/4	5-3/16	3-7/16	8.63
875-422	4X3	5/8	5- 7/16	5-9/32	2-7/8	7- 5/16	7-1/2	10-3/8	5- 1/4	4-3/16	4.07
875-528 ¹	6X2	0	8-23/32	6-11/16	3	10-1/4	9-11/16	12-11/16	7- 9/16	5- 7/16	10.41
875-528F ^{2*}	6X2	1-15/16	9- 3/16	8- 9/16	5- 3/16	10-15/16	11-13/16	17	7- 1/2	2-13/16	10.90
875-530 ¹	6X3	0	8-9/32	6-11/16	3	10-3/16	9-11/16	12-11/16	7- 9/16	5-7/16	10.22
875-530F ^{2*}	6X3	2-15/16	10- 5/16	9- 9/16	6- 3/16	12- 9/16	12-13/16	19	7- 1/2	4- 1/8	13.92
875-532	6X4	0	7-5/8	6-11/16	3	9-7/8	9-11/16	12-11/16	7- 9/16	5- 7/16	9.40
875-578 ¹	8X2	15/32	10-3/16	8-1/4	3-17/32	11-23/32	12-1/4	15-3/4	9-23/32	9-23/32	15.32
875-578F ^{2*}	8X2	7/8	10- 1/2	9- 1/2	5- 1/8	12- 1/4	13- 3/4	18- 7/8	9- 5/8	2-13/16	17.95
875-579F ^{2*}	8X2-1/2	1- 7/16	10-15/16	10- 1/16	5-11/16	12-15/16	14- 5/16	20	9- 5/8	3- 7/16	18.94
875-580F ^{2*}	8X3	1-15/16	11- 5/8	10- 9/16	6- 3/16	13- 7/8	14-13/16	21	9- 5/8	4- 1/8	21.91
875-582	8X4	15/32	9-1/16	8-1/4	3-17/32	11-5/16	12-1/4	15-3/4	9-23/32	5- 1/4	14.31
875-582F ^{2*}	8X4	2-15/16	11- 7/8	11- 9/16	7- 3/16	14- 1/8	15-13/16	23	9- 5/8	5- 3/16	23.96
875-585 ¹	8X6	2-1/32	12-21/32	11-9/32	6-1/32	15-11/16	15-9/32	21-5/16	9-3/4	9-3/4	30.97
875-585F ^{2*}	8X6	4-15/16	13-15/16	13- 9/16	9- 3/16	17- 3/16	17-13/16	27	9- 5/8	7- 1/2	32.96
875-621F ^{2*}	10X2	1/4	11- 7/8	10- 1/2	5	13- 5/8	15- 3/4	20- 3/4	11-15/16	2-13/16	27.04
875-622F ^{2*}	10X2-1/2	1/8	12- 5/16	10- 7/8	5- 3/8	14- 5/16	16- 1/8	21- 1/2	11-15/16	3- 7/16	25.74
875-623 ¹	10X3	3/16	13-17/32	11	4-13/16	15-7/16	16	20-13/16	12-1/16	7-5/8	31.04
875-623F ^{2*}	10X3	3/4	13	11- 1/2	6	15- 1/4	16- 3/4	22- 3/4	11-15/16	4- 1/8	31.80
875-624F ^{2*}	10X4	1- 3/4	13- 1/4	12- 1/2	7	15- 1/2	17- 3/4	24- 3/4	11-15/16	5- 3/16	34.36
875-625F ^{2*}	10X5	3	14-1/16	13-3/4	8-1/4	17-1/16	19	27-1/4	11-15/16	6-5/16	39.20
875-626	10X6	-3/16	11-29/32	11	4-13/16	14-15/16	16	20-13/16	12- 1/16	7-5/8	28.20
875-626F ^{2*}	10X6	3- 3/4	15- 5/16	14- 1/2	9	18- 9/16	19- 3/4	28- 3/4	11-15/16	7- 1/2	42.68
875-628	10X8	1-7/16	12-7/8	12-7/16	6-7/16	16-7/8	17-7/16	23-7/8	12-3/32	9-3/4	35.44
875-628F ^{2*}	10X8	5- 1/4	17- 1/4	16	10- 1/2	21- 1/2	21- 1/4	31- 3/4	11-15/16	9- 5/8	55.18
875-661F ^{2*}	12X2	1- 5/16	13- 3/16	11- 7/16	4-15/16	14-15/16	17-11/16	22- 5/8	14- 1/8	2-13/16	37.57
875-662F ^{2*}	12X2-1/2	15/16	13- 5/8	11-13/16	5- 5/16	15- 5/8	18- 1/16	23- 3/8	14- 1/8	3- 7/16	37.26
875-663F ^{2*}	12X3	1/8	14- 5/16	12- 7/8	6- 3/8	16- 9/16	19- 1/8	25- 1/2	14- 1/8	4- 1/8	43.39
875-664F ^{2*}	12X4	5/8	14- 9/16	13- 3/8	6- 7/8	16-13/16	19- 5/8	26- 1/2	14- 1/8	5- 3/16	49.09
875-666F ^{2*}	12X6	2- 5/8	16- 5/8	15- 3/8	8- 7/8	19- 7/8	21- 5/8	30- 1/2	14- 1/8	7- 1/2	60.92