

## SPECIFICATIONS

- Noise level is measured at a distance of 3.28 ft away from the front of the unit in cooling mode.
- Power consumption is measured when the fan runs at the highest speed setting.
- These specifications are for reference only. For actual data, please refer to the rating label on the back of the unit.

Model	SG-WAC-10ESE-F	SG-WAC-12ESE-F
Power Supply (Ph/V/Hz)	1/115/60	1/115/60
Rated Cooling Capacity (BTU/h)	10,000	12,000
Cooling Power Input (Watts)	930	1110
Rated Current Cooling (Amperage)	8.6	10.3
EER/C.O.P	10.8	10.8
Noise Level dBA (indoor/outdoor)	54/62	56/64
CFM H/M/L	260/240/220	290/270/250
Dehumidifying Capacity	60 Pints per day	81.6 Pints per day
Dimensions (W" x H" x D")	19 x 14.625 x 22.5	19 x 14.625 x 22.5
Package Dimensions (W" x H" x D")	21.5 x 17.375 x 24.625	21.5 x 17.375 x 24.625
Net/Gross Weight (Lbs)	64/73	66/75
Refrigerant Type	R-410A	R-410A

## DISCLAIMER

ALL INFORMATION AND THE TECHNICAL SPECIFICATIONS PRESENTED IN THIS USER'S MANUAL ARE THE PRESENTATION OF THE MANUFACTURER. SOLEUS INTERNATIONAL HAS NOT CONDUCTED INDEPENDENT TEST TO THE INFORMATION AND THE SPECIFICATIONS PRESENTED HEREWITHIN.