Miller DuraFlex® Ultra Series Stretchable Harnesses

Materials

Webbing (DuraFlex).....Polyester,

Urethane Elastomer

Webbing1-3/4" Dacron polyester Minimum Tensile......5000 lbs. on webbing

Grommets.....Brass

Hardware.....Steel Minimum Tensile strength

D-Rings......5000 lbs. (22kN) Buckles.....4000 lbs. (18kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load:.....400 lbs - 181.4 kg

Identification

Label Materials......Lexan and Valeron

Certification

Meets OSHA 1926.502; ANSI A10.14, Z359.1 and CSA Z259.10-M90.

Harness Description Keys

Webbing

D = DuraFlex Stretchable Webbing

P = Polyester Webbing

D-Rings

B = Sliding Back D-Ring

FD = Front D-Ring

F = Front O-Ring

H = Shoulder D-Rings

S = Side Positioning D-Rings

W = Sliding Back web D-Ring

X = D-Ring Web Extension

Special Features

AB = Attached Waist Belt

AL = Adjustable Belt Loops

BL = Belt Loops

BP = Back Pad

BDP = Back D-ring Pad

HP = Shoulder Pads

LP = Leg Pads

LR = Lanyard Ring

RB = Removable Waist Belt

SP = Sub-Pelvic Strap

SR = Self Rescue Loops

SS = Saddle Seat

TO = Tool Belt Buckles

Shoulder/Leg Buckles


FB = Friction Buckles

MB = Mating Buckles

TB = Tongue Buckles







Also available in blue polyester webbing for greater chemical resistance. (Model E650DQC)



Back D-ring Pad	

Quick Connect Buckles

Model No.	Web Type	D-Rings	Shoulder Straps	Leg Straps	Chest Strap	Special Features	Weight
E650QC	D	В	FB	QC	QC	SP, LR,BDP	3.45 lbs. (1.6 kg)
E650QC-7	D	B, S	FB	QC	QC	SP, LR,BDP	3.87 lbs. (1.8 kg)
E650QC-77	D	B, S	FB	QC	QC	BL,SP,LR,BP,RB,BDP	5.60 lbs. (2.5 kg)
E650DQC	D,P	В	FB	QC	QC	SP,LR,BDP	3.45 lbs. (1.6 kg)
E650DQC-7	D,P	B, S	FB	QC	QC	SP, LR,BDP	3.87 lbs. (1.8 kg)
E650DQC-77	D,P	B, S	FB	QC	QC	BL,SP,LR,BP,RB,BDP	5.60 lbs. (2.5 kg)



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com