Miller DuraFlex Python® Harnesses

Models: Python P950 Series

Description

The DuraFlex Python Harness features cushioned tubular webbing in the shoulder straps to minimize possible discomfort around the neck and shoulders, and stretchable DuraFlex webbing in the lower torso, providing greater flexibility, mobility and less fatigue.

Materials

Webbing (DuraFlex): Polyester, Urethane Elastomer

Elastic Keepers: Polyester, Nylon, Lycra

Thread: 6 cord bonded 3 strand polyester

thread. Minimum tensile of 42 lbs

D-ring: Clear Chromate Finished Carbon

Steel

Hardware: Steel Labels: Valeron

Label Pack: Evoprene, Nylon

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max. Working Load:400 lbs (181kg)Webbing Min.Tensile:5,000 lbs (22kN)D-ring Min. Tensile:5,000 lbs (22kN)Buckle Min. Tensile:4,000 lbs (18kN)

Certification

Meets OSHA 1910.66, 1926.502, ANSI A10.32, Z359.1 and CSA requirements.



P950/UGN shown. Also available In blue webbing.

SKU	Side D-Rings	Chest Strap	Shoulder Strap	Leg Straps	Weight	Special Features
P950/UGN	No	Mating	Friction	Mating	3.2 lbs (1.4kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-4/UGN	No	Mating	Friction	Tongue	3.2 lbs (1.5kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-58/UGN	Yes	Mating	Friction	Tongue	4.4 lbs (2.0kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-7/UGN	Yes	Mating	Friction	Mating	3.8 lbs (1.7kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-77/UGN	Yes	Mating	Friction	Tongue	5.6 lbs (2.5kg)	D-ring back pad / Pull-free lanyard rings / Belt loops / Removable tool belt / 6" (152mm) back pad
P950-78/UGN	Yes	Mating	Friction	Mating	5.5 lbs (2.5kg)	D-ring back pad / Pull-free lanyard rings / Belt loops / Removable tool belt / 6" (152mm) back pad

