



Pressure Relief Valves

RV and IRV Series Relief Valve Features:

- Heavy duty no lead bronze, **no lead** brass or 304 stainless steel.
- For shallow, deep well and submersible pumps.
- **Third party certified to NSF/ANSI 372.**
- Spring loaded and pre-set under pressure, **NOT ADJUSTABLE.**
- 1/2" or 3/4" (IRV7575) discharge.



Hamilton Adjustable Safety Relief Valve Features:

- Preset at 75 P.S.I. with concealed adjusting screw to prevent tampering.
- No-lead brass heavy duty, full-flow design with Buna-N seats.



RV-NL Series

ISO 9001



IRV-NL



IRV SS Series



HRV Series

NOTE: Relief valves on this page are not for use with hot water heaters. Recommended for cold water system installations only.

Preset relief valves are **NOT** intended to be adjusted. Any adjustment to preset relief valves voids warranty.

Part Number	Size	Pressure Setting	Ctn/Case	List Price
NO LEAD Bronze Relief Valves - Made in USA				
RV50NL	1/2" x 1/2"	Set at 75 psi	50/150	\$ 30.77
RV75NL	3/4" x 1/2"	Set at 75 psi	50/150	31.22
RV50-100NL	1/2" x 1/2"	Set at 100 psi	50/150	30.77
RV75-100NL	3/4" x 1/2"	Set at 100 psi	50/150	31.22
NO LEAD Brass Relief Valves - Imported				
IRV50NL	1/2" x 1/2"	Set at 75 psi	10/100	12.04
IRV75NL	3/4" x 1/2"	Set at 75 psi	10/100	13.00
IRV50-100NL	1/2" x 1/2"	Set at 100 psi	10/100	12.04
IRV75-100NL	3/4" x 1/2"	Set at 100 psi	10/100	13.00
IRV7575NL	3/4" x 3/4"	Set at 75 psi	10/100	13.46
IRV7575-100NL	3/4" x 3/4"	Set at 100 psi	10/100	13.46
304 Stainless Steel Relief Valves - Imported				
IRV50SS	1/2" x 1/2"	Set at 75 psi	10/100	19.66
IRV75SS	3/4" x 1/2"	Set at 75 psi	10/100	20.76
IRV7575SS	3/4" x 3/4"	Set at 75 psi	10/100	21.50
IRV50-100SS	1/2" x 1/2"	Set at 100 psi	10/100	19.66
IRV75-100SS	3/4" x 1/2"	Set at 100 psi	10/100	20.76
IRV7575-100SS	3/4" x 3/4"	Set at 100 psi	10/100	21.50
Hamilton NO LEAD Brass Adjustable Safety Relief Valves				
		Set at Adjustable to	Sold at Preset Only	
HRV50NL	1/2" mipt x 1/2" fipt	75 psi 150 psi	25	98.33
HRV75NL	3/4" mipt x 3/4" fipt	75 psi 100 psi	25	111.24
HRV125NL	1 1/4" mipt x 1 1/4" fipt	75 psi 200 psi	10	315.00
HRV175NL	1" mipt x 3/4" fipt	75 psi 200 psi	25	185.76

FLOW RATES							
PSI	85	90	95	100	105	110	115
RV Series gpm	.30	7.3	7.7	9.8	17.9	18.9	20.6
IRV Series gpm	2.0	2.7	3.8	4.7	7.0	12.0	12.7
PSI	10	20	30	40	60	80	100
HRV50	.6	1.5	2.5	3.6	6.1	8.8	11.8
HRV75			2.8	5.5	11.0	13.8	17.9
HRV175	6.0	12.6	19.0	24.6	35.6	44.8	52.3
HRV125	12.0	35.0	48.4	69.2	106.5	132.5	150.0



www.americangranby.com

12/4/18

In the United States: Phone (800) 776-2266 Fax (800) 729-3299
 In Canada: Phone (800) 268-7570 Fax (905) 629-3204

1.29