


Pressure Relief Valves

RV and IRV Series Relief Valve Features:

- Heavy duty no lead bronze, **no lead** brass or 304 stainless steel.
- For shallow, deep well and submersible pumps.
- **Third party certified to NSF/ANSI 372.**
- Spring loaded and pre-set under pressure, **NOT ADJUSTABLE.**
- 1/2" or 3/4" (IRV7575) discharge.



Hamilton Adjustable Safety Relief Valve Features:

- Preset at 75 P.S.I. with concealed adjusting screw to prevent tampering.
- No-lead brass heavy duty, full-flow design with Buna-N seats.



RV-NL Series

ISO 9001

Part Number	Size	Pressure Setting	Ctn/Case
NO LEAD Bronze Relief Valves - Made in USA			
RV50NL	1/2"x 1/2"	Set at 75 psi	50/150
RV75NL	3/4"x 1/2"	Set at 75 psi	50/150
RV50-100NL	1/2" x 1/2"	Set at 100 psi	50/150
RV75-100NL	3/4" x 1/2"	Set at 100 psi	50/150



IRV-NL

NO LEAD Brass Relief Valves - Imported

IRV50NL	1/2"x 1/2"	Set at 75 psi	10/100
IRV75NL	3/4"x 1/2"	Set at 75 psi	10/100
IRV7575NL	3/4"x 3/4"	Set at 75 psi	10/100
IRV50-100NL	1/2"x 1/2"	Set at 100 psi	10/100
IRV75-100NL	3/4"x 1/2"	Set at 100 psi	10/100
IRV7575-100NL	3/4"x 3/4"	Set at 100 psi	10/100



IRV SS Series

304 Stainless Steel Relief Valves - Imported

IRV50SS	1/2"x 1/2"	Set at 75 psi	10/100
IRV75SS	3/4" x 1/2"	Set at 75 psi	10/100
IRV7575SS	3/4" x 3/4"	Set at 75 psi	10/100
IRV50-100SS	1/2" x 1/2"	Set at 100 psi	10/100
IRV75-100SS	3/4" x 1/2"	Set at 100 psi	10/100
IRV7575-100SS	3/4" x 3/4"	Set at 100 psi	10/100



HRV Series

Hamilton NO LEAD Brass Adjustable Safety Relief Valves

		Set at Adjustable to		Sold at Preset Only
HRV50NL	1/2" mipt x 1/2" fipt	75 psi	150 psi	25
HRV75NL	3/4" mipt x 3/4" fipt	75 psi	100 psi	25
HRV125NL	1 1/4" mipt x 1 1/4" fipt	75 psi	200 psi	10
HRV175NL	1" mipt x 3/4" fipt	75 psi	200 psi	25

NOTE: Relief valves on this page are not for use with hot water heaters. Recommended for cold water system installations only.

Preset relief valves are NOT intended to be adjusted. Any adjustment to preset relief valves voids warranty.

FLOW RATES							
PSI	85	90	95	100	105	110	115
RV Series gpm	.30	7.3	7.7	9.8	17.9	18.9	20.6
IRV Series gpm	2.0	2.7	3.8	4.7	7.0	12.0	12.7
PSI	10	20	30	40	60	80	100
HRV50	.6	1.5	2.5	3.6	6.1	8.8	11.8
HRV75			2.8	5.5	11.0	13.8	17.9
HRV175	6.0	12.6	19.0	24.6	35.6	44.8	52.3
HRV125	12.0	35.0	48.4	69.2	106.5	132.5	150.0