# INLINE, ANGLE AND TOP ENTRY IRON YOKE CHECK VALVES

(SEE NOTE AT BOTTOM OF PAGE)



Shaded area indicates change Rev. 4-14



H-14245N

5/8x3/4

5/8x3/4

5/8x3/4

5/8

3/4

5/8

3/4

5/8

3/4

Catalog size

Meter size

Tubing size

Category size

Category size Meter size

Tubing size

Pipe size

Meter size

Tubing size

### Angle dual check valve

Inlet: Lock nut

Outlet: Mueller 110™ Conductive Compression Connection for CTS O.D.\* tubing. To order ASSE approved model add suffix (-A) to catalog number.

5/8x3/4x3/4

5/8x3/4, 3/4

Example: H-14245-AN



P-14245N

Angle dual check valve

Inlet: Lock nut

Outlet: MUELLER Pack Joint Connection for CTS O.D.\* tubing. To order ASSE approved model add suffix

(-A) to catalog number. Example: P-14245-AN

Catalog size	5/8x3/4	5/8x3/4x3/4
Meter size	5/8	5/8x3/4, 3/4
Tubing size	3/4	3/4



H-14246N

### Angle dual check valve

3/4

Inlet: Lock nut

Outlet: Copper flare nut

To order ASSE approved model add suffix (-A) to catalog number.

5/8x3/4x3/4

5/8x3/4,3/4

Example: H-14246-AN

E STATE OF THE STA	CARRES

### Angle dual check valve

Inlet: Lock nut Outlet: F.I.P.

To order ASSE approved model add suffix

(-A) to catalog number. Example: H-14248-AN

Catalog size	5/8x3/4	5/8x3/4x3/4
Meter size	5/8	5/8x3/4,3/4
Pipe size	3/4	3/4



H-14247N

Straight dual check val	lve
-------------------------	-----

3/4

Inlet: Lock nut Outlet: F.I.P.

To order ASSE approved model add suffix (-A) to catalog number.

5/8x3/4x3/4

5/8x3/4,3/4

Example: H-14247-AN



H-14464-AN

### Top entry vertical check valve

ASSE approved Inlet: Lock nut Outlet: F.I.P.

To order test valve feature add suffix (-05)

to catalog number

Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	3/4	1	1



H-14466-AN

## Top entry vertical check valve

3/4

ASSE approved Inlet: Lock nut

Outlet: Mueller 110 Conductive Compression Connection for CTS

O.D.\* tubing

To order test valve feature add suffix (-05)

		to catalog number				
Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	5		
Meter size	5/8	5/8x3/4,3/4	5/8x3/4,3/4	5		



P-14466-AN

### Top entry vertical check valve

ASSE approved Inlet: Lock nut

Outlet: MUELLER Pack Joint Connection for CTS O.D.\* tubing To order test valve feature add suffix (-05)

to catalog number

			_								
size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	5/8x1	1	Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	5/8x1	1
ze	5/8	5/8x3/4,3/4	5/8x3/4,3/4	5/8	1	Meter size	5/8	5/8x3/4,3/4	5/8x3/4,3/4	5/8	1
е	3/4	3/4	3/4	1	1	Pipe size	3/4	3/4	3/4	1	1



H-14465-AN

### Top entry vertical check valve

ASSE approved Inlet: Lock nut

Outlet: Copper flare nut

To order test valve feature add suffix (-05)

to catalog number

Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	3/4	1	1



H-14467-AN

### Top entry vertical check valve

ASSE approved Inlet: Lock nut Outlet: M.I.P.

To order test valve feature add suffix (-05) to catalog number

r				
Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pine size	3/4	3/4	1	1

<sup>\*</sup> See charts on page 8B.8 for tubing that may be used with these connections. Note: A complete assembly consists of a bar and expansion wheel from page 8B.1 and inlet and outlet fittings from this section (8B).



April 28, 2017

Subject: Mueller Co. Service Brass

To Whom It May Concern:

This will certify that Mueller Co. service brass, which includes corporation stops, curb stops, service fittings, meter valves, copper meter yokes and end connections, are manufactured and tested in accordance with the latest revision of AWWA C800 standard and are certified to NSF 61.

Components that come in contact with potable water comply with the latest requirements of the U.S. Federal Safe Drinking Water Act that was enacted on January 4<sup>,</sup> 2014.

Sincerely,

Larry Aulich

Senior Product Manager

Harry Centreh

Mueller Company