

Horizontal sidewall sprinklers

Submittal information

Date submitted:

Project Information

| | |
|---------------------------------|-----------------|
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical Data

| | |
|------------------------|-----------------------------------|
| Temp./pressure ratings | 73°F (23°C) at 160 psi (11 bar) |
| | 180°F (82°C) at 100 psi (6.9 bar) |
| | 200°F (93°C) at 80 psi (5.5 bar) |

Product information and application use

Horizontal sidewall sprinklers thread onto Uponor's fire sprinkler adapter fittings. Sprinklers are NSF- and UL-approved for combined plumbing and fire sprinkler systems. Sprinklers designated LF are also NSF Annex G compliant. Note: Protective plastic caps, escutcheons and covers sold separately.



| Part name | Part no. | Weight per UOM [lbs/UOM] |
|--|-----------|--------------------------|
| LF Flat Concealed Horizontal Sidewall Sprinkler, 165F, 4.0 K-factor | LF74000HS | 0.15 |
| LF Recessed Horizontal Sidewall Sprinkler, 155F, 4.2 K-factor, White | LF74300HW | 0.15 |
| LF Recessed Horizontal Sidewall Sprinkler, 175F, 4.2 K-factor, White | LF74301HW | 0.15 |

Installation

Do not store sprinkler assemblies where the ambient temperature will exceed 100°F. Recessed sprinkler wrench required to assemble sprinkler and adapter.

Related applications

AquaSAFE™ Fire Safety Systems

Codes

Standards

Listings

| Trademark Information | Contact Information |
|--|---|
| ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd. | <p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> <p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.636.9517</p> |