


AS 607

ZTC  Other \_\_\_\_\_

**FOUR HOLE CORNER ANGLE**




Std Pkg: 25 · Wt/100 pcs: 78 lbs.

AS 611

ZTC  Other \_\_\_\_\_

**“Z” SUPPORT**

Use With AS 200, AS 210, and AS 500BTB.




Std Pkg: 50 · Wt/100 pcs: 55 lbs.

AS 613

ZTC  Other \_\_\_\_\_

**“U” SUPPORT**

Use With AS 200, AS 210, and AS 500BTB.




Std Pkg: 25 · Wt/100 pcs: 88 lbs.

AS 616

ZTC  Other \_\_\_\_\_

**FOUR HOLE SPLICING CLEVIS**

Use With AS 200 and AS 210.




Std Pkg: 10 · Wt/100 pcs: 265 lbs.

AS 619

SS (Type 304),  ZTC,  Other \_\_\_\_\_

**SQUARE WASHER**



Bolt Size "A"

A	Wt/100 pcs
3/8"	18
1/2"	17
5/8"	16
3/4"	15


Std Pkg: 100 · Wt/100 pcs: See chart above.

AS 624

ZTC  Other \_\_\_\_\_

**TWO HOLE CLOSED ANGLE CONNECTOR**

Angle A = 45°




Std Pkg: 25 · Wt/100 pcs: 58 lbs.

AS 633

ZTC  Other \_\_\_\_\_

**TWO HOLE OPEN ANGLE CONNECTOR**

Angle A = 45°




Std Pkg: 25 · Wt/100 pcs: 58 lbs.

AS 651

ZTC  Other \_\_\_\_\_

**REVERSIBLE STRUT BRACKET**



Std Pkg: Bulk · Wt/100 pcs: See chart above.

A	Load*	Wt/100 pcs
12"	600	293
18"	400	401
24"	300	509

\*Mounted On 12 Ga. Channel.

**LEGEND:**

GR: Powder Coated Supr-Green PG: Pre-Galvanized AL: Aluminum HG: Hot Dipped Galvanized PL: Plain SS: Stainless Steel ZTC: Zinc Trivalent Chromium

PROJECT INFORMATION		APPROVAL STAMP
Project:	<input type="checkbox"/> Approved	
Address:	<input type="checkbox"/> Approved as noted	
Contractor:	<input type="checkbox"/> Not approved	
Engineer:	Remarks:	
Submittal Date:		
Notes 1:		
Notes 2:		