SPEAKMAN®

Alexandria Collection Combination Series SM-6410-P

DESCRIPTION

Speakman Alexandria Collection Combination Series unites the best products included in our Alexandria Series. The combination begins with our anti-scald balanced pressure valve with integral volume control and stops, featuring a brass body and adjustable temperature limit stop. The wall plate, handle, and volume control handle are designed with definitive Alexandria Collection styling. Piston type pressure balancing/ceramic regulating cartridge assembly with built-in check valves. Meets ASME A112.18.1 / CSA B125.1 & ASSE 1016 standards. Also provided is the S-2500 brass 7" shower arm with brass wall flange. The featured product in the Alexandria Collection Combination Series is the ANYSTREAM® S-3011 showerhead with a 4½" outer spray adjustment ring. Five self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. The center core nozzle delivers 12 massaging jets and a combination spray is included. Water-conserving pressure compensating AUTOFLO® device reduces flow to 2.5 GPM / 9.46 LPM maximum, to meet existing ANSI A112.18.1 Standard.

SPECIFICATIONS

SM-6400-P Anti-Scald Balanced Pressure Valve:

Connections: 1/2" female copper sweat inlets & shower outlet; 1/2" NPT female tub outlet

Flow Rate: For use with showerheads rated at 2.0 GPM (7.6 LPM) or higher.

S-3011 Showerhead:

Supply: 1/2" NPT female

Flow Rate: 2.5 GPM / 9.46 LPM MAX

S-2500 Shower Arm:

Supply: ½" NPT male inlet Outlet: ½" NPT male outlet

INSTRUCTIONS

See individual products for installation of the components and warranty information.

S-2500 S-3011 -6'-6" (2 Meters) TO FLOOR (89mm) FINISHED WALL 4-15/16" (125mm)SM-6400-P **LEVER** 1/2 NPT HANDLE (1.4 METERS) 1/2" PLUG TO FLOOR WALL PLATE (13mm)(SHOWER ONLY) 7" DIA SEE NOTE (178mm)2-1/2" TO 3-1/2" (64 - 89mm) NOTE: FOR ADA MOUNTING LOCATIONS CONSULT ADAAG. ANSI A117.1 OR STATE REGULATIONS.

ROUGH-IN

SPEAKMAN®

400 Anchor Mill Rd. New Castle, DE 19720 Phone: 800-537-2107 Fax: 800-977-2747 03/12 Visit us on the web at www.speakmancompany.com IOM-SM-6410