SPEAKMAN° SM-6050-P

Alexandria Shower Combination

FEATURES:

- Alexandria Hand Shower Head VS-3011
- Alexandria Slide bar SA-1102
- Alexandria Pressure Balance Valve and Trim SM-6000-P
- Alexandria Diverter Tub Spout S-1560
- Shower Elbow VS-155
- Trickle Adapter VS-156
- 2.5 gpm (9.5 L/min) flow rate

FINISH:





COMPLIANCE:

• ASME A112.18.1/CSA B125.1 compliant

MODELS:

- ☐ SM-6050-P: with S-1560 diverter tub spout
- ☐ SM-6040-P: without S-1560 diverter tub spout

WARRANTY:

- Consumer Shower Head: Limited Lifetime Warranty
- Commercial Shower head: 1 Year Limited
- Valve: 5 Year Limited
- Accessories: 1 Year Limited



DIMENSIONS: NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified, all inlets and outlets are 1/2" female copper sweat. 3. For ADA mounting locations, consult ADAAG, ANSI A117.1, or static regulations. Contractor pack valves & trim kits available.

VS-155 5-1/2" (140mm)DIA HOLE SHOWER FOR VALVE MOUNTING OUTLET PLATE **COLD WATER** INLET HOT WATER INLET -INTEGRAL STOPS VS-3011 W/ FEMALE INLETS FOR 1/2" COPPER WATER TUBE TLS PLATE - TUB SA-1102 OUTLET, 1'9" (533mm) FINISHED WALL 1/2" NPT SEE NOTE #3 **FEMALE** 5-3/4" (146mm) 4" (102mm) 1" (25mm) WALL PLATE 7" DIA (178mm) TO TOP DIA HOLE 21/2" TO 3-1/2" OF TUB FOR TUB **SPOUT** L 5.1560

W: WWW.SPEAKMAN.COM