


WAX GASKETS, COLD SOLDERS AND LUBRICANTS

PRODUCT

	Stock No.	Size	Packing	Wt. Per Case-Lbs.	UPC Code
	PIPE-LUBE For the lubrication of slip-on or "O" ring type joints with rubber or synthetic rubber type gaskets. NSF Certified. * Aerosol Spray ** Squeeze Tube	*04052 16 oz. **04053 22 fl. oz. 04054 pt. 04055 qt. 04060 gal. 04065 3-1/2 gal. 04070 5 gal. 04072 55 gal.	12 12 12 12 4 1 1 1	17 20 14 28 35 30 43 473	0 54647 04052 3 0 54647 04053 0 0 54647 04054 7 0 54647 04055 4 0 54647 04060 8 0 54647 04065 3 0 54647 04070 7 0 54647 04072 1
	ADHESIVE—LUBE A one component Neoprene* Adhesive Lubricant formulated to improve installation and sealing of compression type gaskets for cast iron soil pipe joints. (*DuPont Reg. Trade Mark) • With Jumbo Dauber in Cap	04080 qt. • 04081 qt.	12 12	27 27	0 54647 04080 6 0 54647 04081 3
	NO-HUB SEALANT A sealant specifically designed as a coating for cast iron pipe to improve leak-free sealing of no-hub couplings. This high performance polymer resin compound is plastic and resists vibration and temperature change. Ideal for lines that need to be air tested. Conforms to MIL-S-45180D •• With Jumbo Dauber in Cap	••04085 qt.	12	27	0 54647 04085 1
	PLASTIC - GASKET SEALANT A sealant specifically designed as a coating to improve leak-free sealing between all kinds of rubber gaskets and all kinds of plastic pipe. This high performance polymer resin compound is plastic and resists vibrations and temperature change. Ideal for lines that need to be air tested. Conforms to MIL-S-45180D. •• With Jumbo Dauber In Cap	••04090 qt.	12	27	0 54647 04090 5
	PLUMBERS GREASE Makes hard turning faucets work smoothly. Lubricates stems of faucets, valves, ball cocks, etc. Waterproof. Will not melt like ordinary grease. For hot water or steam. Temperature range use from -20°F to +350°F. *Hang-Tab Tubes In Display Tray	04095 1 oz. *04096 1 fl. oz. tube 04100 2 oz.	24 12 24	2 1 4	0 54647 04095 0 0 54647 04096 7 0 54647 04100 1
	SILICONE GREASE A 90% pure silicone product that contains no petroleum additives and offers heat resistance up to 450° F. Non-staining. Apply to rubber and synthetic O-rings. * Plastic Bag With Header ** Hang-Tab Tubes In Display Tray	*04114 1/2 oz. 04115 1/2 oz. 04120 1 oz. **04125 1 fl. oz. tube 04126 2 oz. 04130 5 gal.	12 12 12 12 12 1	1 1 2 1 2 45	0 54647 04114 8 0 54647 04115 5 0 54647 04120 9 0 54647 04125 4 0 54647 04126 1 0 54647 04130 8
	SOIL—O Soil pipe cement. Lead substitute in powder form. For caulking soil pipe joints. An economical substitute for lead. Easily mixed with water.	04150 1 lb. 04155 2 lb. 04160 5 lb.	12 12 6	13 26 32	0 54647 04150 6 0 54647 04155 1 0 54647 04160 5
	ANCHORING & PATCHING CEMENT A superior, quick drying, high strength hydraulic cement used for anchoring and patching. Can be used in a wet environment. Sets in 3 to 5 minutes.	04165 3 lb. 04167 10 lb. 04168 20 lb. 04170 50 lb.	6 4 1 1	20 43 21 52	0 54647 04165 0 0 54647 04167 4 0 54647 04168 1 0 54647 04170 4
	TILE GROUT A tile grout in powdered form. A special blend of Portland cements, fortifiers and graded fillers. Suitable for all grouting applications in the areas of floor and wall tile, shower stalls, towel racks, soap dishes, sink tops and mosaic tile applications. One pound will cover 12 to 16 square feet.	04180 2 lb. 04185 10 lb.	12 4	28 43	0 564647 04180 3 0 54647 04185 8