

## Specifications



## Clear Vinyl Tubing

### Product Features

- Crystal clear clarity
- Good flexibility
- Smooth, dense bore maximizes flow and reduces sediment build up.
- Resistance to acids, alkalis and many solvents.
- Typical applications: Drainage lines, aquarium tubing, laboratory tubing, protective insulation.
- Material: Polyvinyl chloride
- Maximum operating temperature: 175° F
- Pressure Range: 19 to 55 psi (131-379 kPa)
- Brittle Point: -40°F (-40°C)
- Hardness: Durometer 83+/-3 Shore A



PF149012N

### Specifications Chart

	I.D.		O.D.		Wall		Length		Working PSI at 70° F
	in.	mm	in.	mm	in.	mm	ft.	m	
PF149012N	1/8	3.175	1/4	6.350	1/16	1.588	100	30.48	55
PF149014N	3/16	4.763	5/16	7.938	1/16	1.588	100	30.48	55
PF149016N	1/4	6.350	3/8	9.525	1/16	1.588	100	30.48	55
PF149022N	3/8	9.525	1/2	12.700	1/16	1.588	100	30.48	45
PF149026N	1/2	12.700	5/8	15.875	1/16	1.588	100	30.48	45
PF149028N	1/2	12.700	3/4	19.050	1/8	3.175	100	30.48	55
PF149030N	5/8	15.875	7/8	22.225	1/8	3.175	100	30.48	40
PF149032N	3/4	19.050	1	25.400	1/8	3.175	50	15.24	35
PF149034N	1	25.400	1-1/4	31.7500	1/8	3.175	50	15.24	25

### Notes

PROFLO vinyl tubing is not recommended for esters, ketones and some aromatics. PROFLO vinyl tubing should not be used for repairs or installation of dishwasher supply or discharge lines or on ice maker applications.

### Warranty and Codes

This PROFLO product carries a 1-year limited warranty.