

ROOM AIR SPECIFICATIONS

FEDDERS

PROFORMANCE

ELECTRICAL REQUIREMENTS

FEATURES

CABINET SIZE

WINDOW OPENING


WEIGHT

Model	Energy Star	Cooling area (See Note 1)		BTU Cooling	BTU Heating	EER	PINTS PER HOUR		ROOM AIR DELIVERY (CFM MAX)	VOLTAGE	Amps Cooling	Amps Heating	Watts Cooling	Watts Heating	Plug Cap. Amps	Receptacle	Air Exchanger	Air Direction	Fan Speeds	Auto Restart	slide-Out Chassis	Additional Features	Width	Depth	Height	Width (min-Max)	Height (Min)	NetShip Weight
Window Air Conditioners																												
R05F2A	N	150	5000			9.7	0.8	118	115	4.8			515		10	A	N	2 Way	2	N	N	M	16	13 1/4	12 5/16	16 1/2-36	13	35/40
R05F2A	N	150	5000			9.7	0.8	118	115	4.8			515		10	A	N	2 Way	3	Y	N	*	16 1/4	13 3/4	12 5/16	16 1/2-36	13	35/40
R05F2A	Y	150	5000			10.7	1.1	147	115	4.5			485		10	A	N	2 Way	3	Y	N	*	16 1/4	15 3/4	12 5/16	16 1/2-36	13	39/45
R06F2A	N	200	6000			9.7	1.3	147	115	6.1			620		10	A	N	4 Way	3	Y	N	*	16 1/4	15 3/4	12 5/16	16 1/2-36	13	40/46
R06F2A	Y	200	6000			10.7	1.3	147	115	5.4			560		10	A	N	4 Way	3	Y	N	*	16 1/4	15 3/4	12 5/16	16 1/2-36	13	47/55
R08F2A	N	340	8000			9.8	1.7	224	115	7.4			815		10	A	N	4 Way	3	Y	N	*	18 5/8	15 3/4	13 5/16	21 15/16-36	14	47/53
R08F2A	Y	340	8000			10.8	1.7	224	115	7			740		13	A	N	4 Way	3	Y	N	*	18 5/8	15 3/4	13 5/16	21 15/16-36	14 1/2	47/54
R10F2A	N	450	10000			9.8	2.4	295	115	9.4			1020		13	A	N	4 Way	3	Y	N	*	19	19 3/16	14 3/4	22 3/16-36	14 1/2	57/67
R10F2A	Y	450	10000			10.8	2.7	295	115	8.8			930		15	A	N	4 Way	3	Y	N	*	19	19 3/16	14 3/4	22 3/16-36	14 1/4	83/92
Y12F2A	Y	550	12000			10.8	2	280	115	9.7			1110		15	A	Y	4 Way	3	Y	Y	*	22 5/8	21 7/16	15 3/8	22 7/8-36	16 1/4	83/91
Y12F7A	Y	550	12000			10.8	2.2	280	230	4.9			1130		15	B	Y	4 Way	3	Y	Y	*	22 5/8	21 7/16	15 3/8	22 7/8-36	16 1/4	99/112
Y15F2A	Y	800	15000			10.7	3.8	460	115	12			1410		15	A	Y	4 Way	3	Y	Y	*	23 5/8	25 1/2	17 13/16	23 7/8-40 1/2	18 1/2	99/111
Y18F7A	Y	1000	18000			10.7	5.5	460	230	7.7			1730		15	B	Y	4 Way	3	Y	Y	*	23 5/8	25 1/2	17 13/16	23 7/8-40 1/2	18 1/2	108/122
R24E7A	Y	1400	24000			9.4	8	530	230	12			2660		20	C	Y	4 Way	3	Y	Y	*	26 1/2	25 1/2	18 1/2	26 13/16 - 42	19	126/137
HEAT / COOL WINDOW AIR CONDITIONERS																												
Y08F2B	N	340	8000	3500		9.8	1.5	280	115	6.6	11.6	740	1290	13	A	Y	4 Way	3	Y	Y	*	23	23 2/5	15 5/8	23 7/8-36	16 1/4	72/80	
Y12F2B	N	550	12000	10200		9.8	2.2	280	230	4.9	15	1130	3500	20	C	Y	4 Way	3	Y	Y	*	23	23 2/5	15 5/8	23 7/8-36	16 1/4	81/89	
Y18F7C	N	1000	18000	10200		9.7	5.5	460	230	8.4	22	1900	3500	20	C	Y	4 Way	3	Y	Y	*	23 5/8	25 1/2	17 15/16	23 7/8-40 1/2	18 1/2	105/119	
R24E7A	N	1400	24000	16000		9.4	8	530	230	12	22.5	2660	4900	25	D	Y	4 Way	3	Y	Y	*	26 1/2	25 1/2	18 1/2	26 7/8 - 42	19	128/142	
THROUGH THE-WALL AIR CONDITIONERS																												
T08W2A	Y	340	340			9.4	1.8	283	115	8			850		10	A	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	60/71
T10W2A	Y	450	450			9.4	2.6	283	115	9.8			1060		15	A	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	65/75
T10W7A	Y	450	450			9.4	2.8	295	230	5.1			1060		15	B	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	61/71
T12W2A	Y	550	550			9.4	3.3	295	115	11			1240		15	A	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	68/76
T12W7B	Y	550	550			9.4	3.5	295	230	6.3			1270		15	B	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	69/79
T12W7B	N	550	550	10200		9.4	3.5	295	230	6	15	1330	3450	20	C	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	73/83	
T14W7B	N	700	700			9	4.3	318	230	7.4			1550		20	C	N	4 Way	3	Y	Y	**	24 1/16	20 1/4	14 1/2	N/A	N/A	69/80
THROUGH THE-WALL AIR CONDITIONERS FOR A & B SLEEVES																												
A09W2A	Y	400	9200			9.8	2.4	280	115	8.6			940		15	A	N	4 Way	3	Y	Y	**	26	16 7/8	15 5/8	N/A	N/A	84/97
A12W2A	Y	550	11800			9.4	3.2	280	115	12			1260		15	A	N	4 Way	3	Y	Y	**	26	16 7/8	15 5/8	N/A	N/A	84/97
A12W7A	Y	550	11800			9.8	3.2	280	230	5.6			1260		13	A	N	4 Way	3	Y	Y	**	26	16 7/8	15 5/8	N/A	N/A	84/97
PORTABLE AIR CONDITIONERS																												
P09S2A	N	400	9000			8.8	3	185	115	9.5			1080		15	A	N	1 Way	3	Y		***	17 1/8	15 1/2	31 5/16	N/A	N/A	66/75
HP12D2A	N	550	12000	11000		8.7	4	235	115	10.8	11	1300	1250	15	A	N	2Way	3	Y		****	18 7/8	18 1/2	36 5/8	N/A	N/A	79/94	

Note 1 The square feet of cooling area listed is based on average room conditions in a moderate climate. Some exceptions are kitchens (add 4000 BTU), high ceilings or unusual floor plans (increase 10 - 20 percent)

ADDITIONAL FEATURES

- M MECHANICAL CONTROL, NO REMOTE CONTROL
- * Full function remote control, 24 hour timer on-off, sleep mode, Energy Saver mode, LED display, C/F display change, filter check (250 hours)
- Auto Rstart function, Operation Mode: Cool/Fan/Dry/Auto, Easy mount window kit
- ** full function remote, 24 hour on-off timer, Sleep Mode, Energy saver mode, LED display, C/F display change, auto restart function, operation Mode: Cool/Fan
- *** Simple Remote Control, 12 hour timer on-off, LED Display, Auto Restart
- **** Simple Remote Control, 24 hour timer on-off, LED Display, Auto Restart



Models and specifications are subject to change without notice. All models have electronic controls unless noted otherwise. 230v models are 208/230 Volt and specifications are listed as 230v.

www.fedders.com

Airwell-Fedders North America, Inc.

2500 City West Blvd

Suite 300

Houston, Texas 77042