

No. 10-DR Drain Elbow

PRODUCT DESCRIPTION




See Victaulic
publication 10.01
for details.

No. 10-DR drain elbows are specifically designed for use on fire protection standpipes. The drain is drilled and tapped for a 1" (25 mm) NPT outlet.

Constructed of durable ductile iron all sizes conform to the ratings of Style 77 couplings. No.10-DR elbows are supplied with grooves or shoulders. These fittings are not intended for use with Victaulic Plain End couplings.

When connecting wafer or lug-type butterfly valves directly to Victaulic drain elbows with Style 741 or 743 Vic-Flange® adapters or Style 744 FireLock® Flange adapters, check disc clearance dimensions with the I.D. dimension of the fitting.

DIMENSIONS



Fitting Size		Dimensions Inches/millimeters			Approximate Weight Each Lbs./kg
Nominal Outside Diameter Inches/mm	Actual Outside Diameter Inches/mm	C - E	H	P	
2 1/2 65	2.875 73,0	3.75 95	2.75 70	1.68 43	5.2 2,4
3 80	3.500 88,9	4.25 108	2.75 70	2.10 53	5.3 2,4
4 100	4.500 114,3	5.00 127	2.75 70	2.60 66	8.8 4,0
6 150	6.625 168,3	6.50 165	2.75 70	3.65 93	18.7 8,5

MATERIAL SPECIFICATIONS

Housing: Ductile iron conforming to ASTM A-536, grade 65-45-12. Ductile iron conforming to ASTM A-395, grade 65-45-15, is available upon special request.

Fitting Coatings: Orange enamel

- **Optional:** Hot dip galvanized and others.

This product shall be manufactured by Victaulic Company. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.