

Portable Pressurized and On-Site Eyewashes

On-Site Heater Jacket Retrofit Kit



□ S19-921HR (pedestal not included)

- Protects against freezing down to -20°F (-29°C)
- Insulated heater jacket conceals a 121-watt heater
- Secondary thermostat prevents overheating if primary thermostat fails
- All UL-listed components; requires 120-volt AC

On-Site Waste Cart



□ S19-399

- · High-visibility yellow
- Captures used fluid; 56-gallon capacity
- Tapered sump, easy to drain

Heater Jacket Retrofit Kits for Portable Pressurized **Eyewash Tanks**



Thermostatically controls water in weather conditions down to -10°F (-23°C); uses standard 120 VAC. Tanks not included

□ S19-671HR (shown at right)

Heater jacket retrofit kit for 5-gallon tank

□ S19-690HR (shown at left)

Heater jacket retrofit kit for 10-gallon tank

□ S19-788HR (shown at center)

Heater jacket retrofit kit for 15-gallon tank

Transport Cart for Pressurized Eyewash Tanks



□ S19-690A

Four-wheel stainless steel transport cart. For use with eyewash tanks without heater jackets (eyewash tanks not included)

Drench Hose Spray Kits



☐ S19-430EH

Drench hose spray kit with valve, drench hose sprayhead, hose, inspection tag and hardware. For use with eyewashes; provides a body water drench



□ S19-430SH

Drench hose spray kit with valve, drench hose sprayhead, hose, inspection tag and hardware. For use with drench showers; provides a body water drench



Emergency Fixtures Accessories

Emergency Signaling Systems

- · Automatic, audible and visual alarm system
- Horn and signal light activate when unit is in use; preassembled
- NEMA 1, 3R, 4 and 4X signaling system options
- Central control board powers all options

- · Recessed, wall-mount or mount on safety fixture
- Universal AC input: 90-264 AC, 50-60 Hz
- Double pole, double throw flow switch
- 1/2" (13mm) or 1-1/4" (32mm) NPT inlet piping

Standard Signaling Systems \$19-322 Series

□ S19-322D

Recessed NEMA 1. shower/ combination signaling system, bright LED beacon/signal light

□ S19-322E

Recessed NEMA 1, eye or eye/face wash signaling system, bright LED beacon/signal light

S19-323 Series

□ S19-323D

NEMA 3R, shower/combination signaling system, amber signal light

□ S19-323E

NEMA 3R, eye or eye/face wash signaling system, amber signal light

S19-324 Explosion **Proof Series**

□ S19-324D1D

Class I, Division 1, Groups B, C and D, NEMA 4, shower/combination signaling system, amber signal light

□ S19-324D2D

Class I, Division 2, Groups B, C and D, NEMA 4, shower/combination signaling system, amber signal light

S19-324 General Area Series

□ S19-324D

NEMA 4X, combination/shower signaling system, amber signal light, silence switch with auto reset

□ S19-324E

NEMA 4X, eye or eye/face wash signaling system, amber signal light, silence switch with auto reset

□ S19-324DG

NEMA 4X, shower/combination signaling system, amber signal light, silence switch with auto reset, green beacon light

□ S19-324EG

NEMA 4X, eye or eye/face wash signaling system, amber signal light, silence switch with auto reset, green beacon light

□ S19-324DGW

NEMA 4X, shower/combination signaling system, amber signal light, silence switch with auto reset, green beacon light, white area light

□ S19-324EGW

NEMA 4X, eye or eye face wash signaling system, amber signal light, silence switch with auto reset, green beacon light, white area light



Model S19-324DGW shown

Custom Signaling System

\$19-324 Series Configurator

□ S19-324

General area, NEMA 4X rated

□ S19-324D1*

Class I, Division 1; Groups B, C and D, NEMA 4 or 4X rated

□ S19-324D2*

Class I, Division 2; Groups B, C and D, NEMA 4 or 4X rated



For a list of all configurable options, see the Emergency Signaling System technical data sheets at www.bradlevcorp.com

*Optional selection of reset switch may impact electrical rating





Shower Accessories

Privacy Curtain



□ S19-330

- Provides privacy to shower user in emergency situations
- · Universal mounting
- 3-ply, vinyl laminate, curtain reinforced at top and bottom
- Chemical and mildew resistant; waterproof
- High-visibility yellow color
- Dimensions: 70"L x 145"W
- Stainless steel, corrosion resistant curtain rail and mounting brackets
- Rail dimensions: 1½" x 42" diameter
- Not compatible with barrier-free, PVC and heat trace units – contact Bradley for more information

Drench Shower Tester



□ S19-330ST

- Heavy-duty tester for required weekly activation
- Watertight funnel with weighted bottom
- 84" long with 8' telescoping aluminum handle
- Includes testing record card

Classic Accessories

Retrofit Classic Dust Covers



□ **S45-1964**

For use with any Bradley plastic eyewash bowl. Plastic bowl, dust cover, gasket and hardware



□ S45-2396

For use with any Bradley eyewash bowl. Stainless steel "clam shell" cover and bowl, stainless steel handle, tether and quick release pin