

INSTALLATION INSTRUCTION FOR 5173

For Wall Mount Light Fixtures

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DUDISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture and all mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any parts necessary for installation.

MOUNTING THE FIXTURE (Fig.1)

3. Secure the hanging bracket (A) to outlet box with the junction box screws (B) (Size: #8-32*0.6"L) The side of the hanging bracket marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

4. At this point, connect the electrical wires as shown in figure 2, making sure that all wire connectors are secured. If the junction box has a ground wire (green or bare copper), connect the ground wire to it. Otherwise, connect the fixture's ground wire directly to the hanging bracket with the green screw provided. After wires are connected, tuck them carefully into the junction box.

COMPLETING THE INSTALLATION

5. Mount the mounting back plate (D) to hanging bracket (A), and then secure with mounting screws (C) (Size: #8-32*0.3"L) .
6. Place glass (F) over socket (E), then secure with socket ring (G) by wrench (H).
7. Install the light bulb(s) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

Return the power to the junction box and test the fixture. Your installation is now complete.

Note: Illustrations (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig.1




Fig.2

