

# **Underscore®**

5' VibrAcoustic® Bath K-1167-VB



### **Features**

- End drain.
- Slotted overflow for deep soaking.
- VibrAcoustic® technology emits sound waves and offers a surround sound experience.
- Six transducers and a control amplifier with 25' (7.6 m) of wiring.
- High-resolution color screen in polished chrome.
- Integral lumbar support.
- 60" (1524 mm) x 30" (762 mm) x 19" (483 mm)

### **Material**

Acrylic

### Installation

Drop-in or under-mount.

## **Required Accessories**

K- 7271 Brass Slotted Overflow Bath Drain K- 7272 PVC Slotted Overflow Bath Drain

### **Recommended Accessories**

1184460 Kit, UI Mounting K- 1491 Bath/Whirlpool Pillow K- 1601 Bath/Whirlpool Footstop K- 531 Under-mount Installation Kit



### Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2 Greenguard UL 2818 - Gold ADA ICC/ANSI A117.1 CARB P2

# **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

#### Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™






## **Underscore®**

5' VibrAcoustic® Bath

K-1167-VB



## **Required Electrical Service**

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Amplifier: 120 V, 15 A, 50/60 Hz

#### **Technical Information**

All product dimensions are nominal.

Installation: 3-Wall Alcove

Drain location: End

Basin area, bottom: 42-3/8" x 20" (1076 mm x 508 mm)
Basin area, top: 54-3/8" x 24-5/16" (1381 mm x 618 mm)

Weight: 75 lbs (34 kg)

Minimum floor load: 50 lbs/ft² (244.1 kg/m²)

Water depth: 15-1/16" (383 mm)

Water capacity: 59.8 gal (226.4 L)

Cutout: Drop-in, 59-1/2" x 28-1/2" (1511 mm x

724 mm)

Electrical component Amplifier: 120 V, 50/60 Hz, 15 W

rating:

Minimum flat for door: 2-1/2" (63 mm)

#### **Notes**

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Provide one grounded electrical outlet within 24" (610 mm) of each component.

Control amplifier fits 16" (406 mm) center studs. 25' (7.6 m) cables are included.

ADA compliant when installed to the specific requirements of these regulations.

