

EC501 END CAP COUPLING

SUBMITTAL INFORMATION



STANDARD

Romac RC501 couplings meet the specifications set forth in the AWWA Standard C219 coupling spec.

MATERIALS

CASTINGS

The end rings and center rings are cast from ductile (nodular) iron, meeting or exceeding ASTM A 536.

END CAP

End caps are furnished with 2" IPT female threads with plug.

GASKETS

Gaskets are made from virgin Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 MBA 710. Other compounds available for petroleum, chemical, or high temperature service.

BOLTS AND NUTS

5/8 inch, High strength low alloy steel trackhead bolts. National coarse rolled thread and heavy hex nuts. Steel meets AWWA C111 composition specifications. Stainless steel bolts and nuts available on request.

COATINGS

Shop coat applied to cast parts for corrosion protection in transit. Fusion bonded epoxy, liquid epoxy and other coatings available on request.

PRESSURE

When properly installed on a pipe that is within the correct outside diameter range, couplings in the Romac Style 501 line can be used at working pressures up to 260 psi. Higher working pressures available for specific applications.

SIZES & RANGES

See catalog.

1/17

Document # 20-8-0043

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.