

ENDOT INDUSTRIES

PIPE AND TUBING

EndoPure PE-4710

BLUE (with CLEAR CORE) COILED PIPE & TUBING

BLUE WATER SERVICE TUBING (CTS - O.D. CONTROLLED) - ASTM D2737-12

| Size | Nominal O.D. | Nominal I.D. | Min. Wall | Weight Per 100' | Standard Coil Size | Part Number |
|---|--------------|--------------|-----------|-----------------|--------------------|----------------|
| STANDARD OUTSIDE DIMENSION RATIO (SODR) = 9 (250 PSI) | | | | | | |
| 3/4" | 0.875 | 0.675 | .097 | 10.3 | 500/100 | PEP07541010009 |
| 1" | 1.125 | 0.865 | .125 | 17.1 | 300/100 | PEP10041010009 |
| 1-1/4" | 1.375 | 1.059 | .153 | 25.5 | 300/100 | PEP12541010009 |
| 1-1/2" | 1.625 | 1.253 | .181 | 35.3 | 300/100 | PEP15041010009 |
| 2" | 2.125 | 1.629 | .236 | 61.0 | 200/100 | PEP20041010009 |

BLUE WATER SERVICE PIPE (IPS - I.D. CONTROLLED) - ASTM D2239-12

| Size | Nominal O.D. | Nominal I.D. | Min. Wall | Weight Per 100' | Standard Coil Size | Part Number |
|--|--------------|--------------|-----------|-----------------|--------------------|----------------|
| STANDARD INSIDE DIMENSION RATIO (SIDR) = 7 (250 PSI) | | | | | | |
| 3/4" | 1.070 | 0.824 | .118 | 15.5 | 400/100 | PEP07541010004 |
| 1" | 1.359 | 1.049 | .150 | 24.9 | 300/200/100 | PEP10041010004 |
| 1-1/4" | 1.785 | 1.380 | .197 | 42.8 | 300/100 | PEP12541010004 |
| 1-1/2" | 2.086 | 1.610 | .230 | 58.4 | 250/100 | PEP15041010004 |
| 2" | 2.675 | 2.067 | .295 | 93.3 | 200/100 | PEP20041010004 |
| STANDARD INSIDE DIMENSION RATIO (SIDR) = 9 (200 PSI) | | | | | | |
| 3/4" | 1.026 | 0.824 | .014 | 12.1 | 400/100 | PEP07541010003 |
| 1" | 1.293 | 1.049 | .120 | 19.5 | 300/100 | PEP10041010003 |
| 1-1/4" | 1.710 | 1.380 | .157 | 33.2 | 300/100 | PEP12541010003 |
| 1-1/2" | 1.980 | 1.610 | .179 | 42.9 | 250/100 | PBJ15041010003 |
| 2" | 2.540 | 2.067 | .230 | 71.0 | 200/100 | PBJ20041010003 |

BLUE WATER SERVICE PIPE (IPS - O.D. CONTROLLED) - ASTM D3035

| Size | Nominal O.D. | Nominal I.D. | Min. Wall | Weight Per 100' | Standard Coil Size | Part Number |
|--|--------------|--------------|-----------|-----------------|--------------------|----------------|
| STANDARD OUTSIDE DIMENSION RATIO (DR) = 9 (250 PSI) | | | | | | |
| 3/4" | 1.050 | 0.816 | .117 | 15.2 | 400/100 | PEP07541010016 |
| 1" | 1.315 | 1.029 | .146 | 22.7 | 300/200/100 | PEP10041010016 |
| 1-1/4" | 1.660 | 1.294 | .184 | 36.5 | 300/100 | PEP12541010016 |
| 1-1/2" | 1.900 | 1.478 | .211 | 47.8 | 300/100 | PEP15041010016 |
| 2" | 2.375 | 1.847 | .264 | 74.1 | 200/100 | PEP20041010016 |
| STANDARD OUTSIDE DIMENSION RATIO (DR) = 11 (200 PSI) | | | | | | |
| 3/4" | 1.050 | 0.860 | .095 | 13.5 | 400/100 | PEP07541010014 |
| 1" | 1.315 | 1.075 | .120 | 19.9 | 300/200/100 | PEP10041010014 |
| 1-1/4" | 1.660 | 1.358 | .151 | 31.4 | 300/100 | PEP12541010014 |
| 1-1/2" | 1.900 | 1.554 | .173 | 41.1 | 250/100 | PEP15041010014 |
| 2" | 2.375 | 1.943 | .216 | 65.9 | 200/100 | PEP20041010014 |

CONFORMS TO THE FOLLOWING APPLICABLE STANDARDS

| | |
|---------------------------|--|
| NSF | Listed Under Standard 14 & 61 for Potable Water |
| ASTM D3350 | Cell Classification 445576A (A = Raw Material before processing) |
| ASTM D2737, D2239 & D3035 | Meets PE 4710 Requirements |
| AWWA C901 | Conforms as 250 PSI & 200 PSI |
| BOCA | Conforms as 250 PSI & 200 PSI |

WARRANTY

Certification of Purity and Lifetime Warranty. See Warranty for Details.



CORPORATE HEADQUARTERS

60 Green Pond Road
Rockaway, NJ 07866
800-443-6368 • FAX 973-625-4087

ENDOT INDUSTRIES, INC.

www.endot.com • e-mail: info@endot.com

PLANT LOCATIONS

Greeneville, TN
Pryor Creek, OK