



PROWLER LD-5000

ELECTROCHEMICAL LEAK DETECTOR

Featuring manual calibration mode and reset control, the highly sensitive PROWLER detects all HFC, HFO, HCFC and blended refrigerants—finding even the smallest of leaks

FEATURES

- Sensor life > 10 years
- High, medium, and low sensitivity settings
- Mutable alarm with silent vibrating handle
- Warm up time < 30 seconds; response time immediate
- Back-lit LCD screen tilts up for easy viewing at any angle
- Leak indicator bar graph displays leak intensity
- 17" flexible probe
- Operates with four AA batteries (included)
- Certifications include: CE, ASHRAE 173-2012, EN 14624:2012, SAE J2791 and SAE J2913
- Carrying case (included)
- 2 year warranty

PART NO.	DESCRIPTION
LD-5000	Prowler leak detector in case
LD-S100	Replacement sensor (3 prong)
LD-S101	Replacement sensor (6 prong)
LD-RF5	Replacement filters (5 pack)
LD-TV	Replacement leak test vial
LD-PK	Parts kit (6-prong sensor, filter kit and test vial)
LD-CS	Carrying case

SENSITIVITY

R1234yf	.0125 oz/yr
R22	.025 oz/yr
R134a	.05 oz/yr
R404A	.05 oz/yr
R407A	.05 oz/yr
R410A	.05 oz/yr
R427A	.05 oz/yr



JB INDUSTRIES

800.323.0811 JBIND.COM SALES@JBIND.COM