



**ThermaSleeve™**



### APPLICATIONS

Energy efficient pipe insulation in either metallized or polyethylene sleeve. Thick insulation blanket with R-values of 4.2, 6.0, and 8.0. Fast and economical to install over round sheet metal duct. UL classified for pipe and equipment covering.

Made with Owens Corning™ EcoTouch® formaldehyde-free Insulation. Made with 99% natural materials and highest recycled content. Also, it is the only fiberglass insulation listed in the USDA BioPreferred Catalog.

### THERMASLEEVE SPECS

Permeability Rating:	0.1
Flame Spread:	Less than 25
Smoke Developed:	Less than 50
Length:	5' standard
Diameters:	4, 5, 6, 7, 8, 10, 12, 14, 16 and 18 inches
R-Value:	4.2, 6.0, and 8.0



The Pink Panther™ & © 1964-2008 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a Registered trademark of Owens Corning. ©2008 Owens Corning.



Worldwide Sales Headquarters & Customer Service Department  
381 Carwellyn Rd. • Abbeville, SC 29620  
In the US, call 1-800-459-4822 • In Canada, call 1-800-263-3539 • [thermaflex.net](http://thermaflex.net)