

**CONCEALED TRAPWAY CADET® 3 FloWise®
RIGHT HEIGHT® ROUND FRONT TOILET**

- ☐ **2988.101**
 - Vitreous china
 - Meets definition for HET (High Efficiency Toilet)
 - High efficiency (4.8 Lpf/1.28 gpf)
 - Meets EPA WaterSense® criteria
 - 305mm (12") rough-in
 - 16-1/2" rim height for accessible applications
 - EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold, and mildew on the surface
 - Features the **Cadet® 3 Flushing System**
 - Round Front siphon action jetted bowl with smooth-sided, concealed trapway
 - Generous 9" x 8" water surface area
 - PowerWash® rim scrubs bowl with each flush
 - Oversized 3" flush valve
 - Chrome-plated trip lever
 - Includes top mounting, plastic Slow-Close seat and cover with easy lift-off feature for simple removal and attachment for cleaning, packed with bowl
 - 2 color-matched bolt hole covers
 - Lifetime warranty on chinaware, 5 year warranty on all mechanical parts, and 1 year warranty on seat
- ☐ **2988.813** Same as above except with trip lever on right hand side
- ☐ **3053.000** Right Height® Round Front Bowl with Seat
- ☐ **4000.101** Tank
- ☐ **4000.813** Tank with right hand trip lever
- ☐ **5024B.65G** Preferred Seat: Transitional Round Front Luxury Seat

Nominal Dimensions:

28-1/4" x 15-3/4" x 30-3/4"
(718 x 400 x 781mm)

Fixture and toilet seat only, supply by others

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2/CSA B45.1-08 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HET's



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- ☐ Color: ☐ White
- ☐ Supply with stop:



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES
AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND
USABLE BUILDING FACILITIES-CHECK LOCAL CODES.

