

### M12™ Cable Stripper Kit

2435CU-21, 2435AL-21, 2435X-21 (2435-20 Tool-Only)

### Specifications:

Yes
Yes
Industry Standard Quick-Change
8.6" x 2.8" x 11.5"
3.6 lbs

Includes: 2435CU-21 1/0 AWG - 750 MCM Cu THHN / XHHW Bushings; **2435AL-21** 1/0 AWG - 750 MCM AI THHN / XHHW Bushings: 2435X-21 1/0 AWG - 500 MCM Cu RHW / RHH / USE Bushings; All Kits Include: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

#### Reference Available Bushings on Pg. 62



### M12™600 MCM Cable Cutter Kit

2472-21XC (2472-20 Tool-Only)

Specifications:		
Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable	
Jaw Opening	1-7/16"	
Two-Speed	Yes	
Length / Weight	10.5" / 6.7 lbs	(C)

Includes: (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, Multi-Voltage Charger, Carrying Case

# Related Accessory: 48-44-0410 M12™ 600 MCM Cable Cutter Blade

### M12™ Plastic Pipe **Shear Kit**

2470-21 (2470-20 Tool-Only)

### Encoifications

Specifications:	
Cut Capacity	Up to 2" Schedule 80 PVC
Torque	1,900 in-lbs
Blade	3 mm Reinforced Stainless Steel
Length / Weight	14.4" / 4.4 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack, Charger, Carrying Case

## Related Accessory:

**48-44-0405** M12<sup>™</sup> Plastic Pipe Shear Blade

#### M12™ Copper Tubing **Cutter Kit**

2471-22, 2471-21 (2471-20 Tool-Only)

Specifications:		0
Cut Capacity	3/8" - 1" (1/2" - 1-1/8" O.D.)	
Tubing Type	M, L and K Copper	
RPM	500	
Length / Weight	14.0" / 3.2 lbs	

**Includes: 2471-22** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs; **2471-21** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack;

All Kits Include: Charger, Carrying Case

Related Accessory: 48-38-0010 Copper Cutter Wheel (2-Pack)

### M12™ Drain Snake Kit

2571-21 (2571-20 Tool-Only)

#### Specifications:

Specifications	
Max Drain Line Capacity	1-1/4" – 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack, 5/16" x 25' Inner Core Bulb Head Cable with Inner Drum, Charger, 5 Gallon Storage Bucket

#### **Related Accessories:**

48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating; 48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating; 48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating;

48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating

## M12™ TRAPSNAKE™ 6¹ Toilet Auger Kit 2576-21 (2576-20 Tool-Only)


#### **Specifications:**

RPM	0 – 500
Cable Lock	Yes
Cable Size	6' x 1/2"
Cable Head	Retriever Bulb
Replacement Cables	Available
Weight	9.0 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack, Cable, Charger

#### **Related Accessories:**

48-53-2576 TRAPSNAKE™ 6' Toilet Auger Replacement Cable; 48-22-2576 TRAPSNAKE™ Toilet Auger Case; 2575-21 M12™ TRAPSNAKE™ Driver Upgrade Kit



### M12™ TRAPSNAKE™ 4' Urinal Auger Kit

2574-21 (2574-20 Tool-Only)

## Specifications:

pecifications	i i	
RPM	0 – 500	
Cable Lock	Yes	
Cable Size	4' x 3/8"	
Cable Head	Bulb	
Replacement Cables	Available	
Weight	6.4 lbs	

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger **Related Accessories:** 

**48-53-2577** TRAPSNAKE<sup>™</sup> 4' Urinal Auger Replacement Cable; 48-22-2577 TRAPSNAKE™ Urinal Auger Case; **2575-21** M12<sup>™</sup> TRAPSNAKE<sup>™</sup> Driver Upgrade Kit

### M12™ AIRSNAKE™ **Drain Cleaning Air Gun Kit**

2572B-21, (2572B-20 Tool-Only)

Specifications:		
Max Drain Line Capacity	1" – 4", Up to 35'	Milwaukee
Automatic Pressure Loading	Yes	AIRSNA
Variable Pressure	0 - 50 PSI	
Variable Pressure Dial	Yes	
LED Light	Yes	
Length / Weight	20.8" / 7.1 lbs	

Includes: 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charge

All Kits Include: 2572B-20: 1" - 2" Drain Plug, 2" - 3" Drain Plug, 3" - 4" Drain Plug, Drain Shroud Attachment, Toilet Seal Attachment, 10" Extension, (3) Straight Connectors, 15° Offset Connector, Carrying Case



### M12™ ProPEX® Expansion Tool Kit

2432-22XC, 2432-22 (2432-20 Tool-Only)

### Specifications:

opeoinou de dionoi	
Capacity	3/8" - 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" - 1" M12™ / Uponor
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs

Includes: 2432-22XC (2) M12™ REDLITHIUM™ XC3.0 Battery Packs; 2432-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs:

All Kits Include: (3) ProPEX® Expansion Heads (1/2", 3/4", 1"), Grease, Multi-Voltage Charger, Carrying Case

### **Related Accessories:**

49-08-2400 ProPEX® Expander Cone Grease; 49-16-2403 3/8" ProPEX® Expansion Head; 49-16-2404 1/2" ProPEX® Expansion Head; 49-16-2405 5/8" ProPEX® Expansion Head; 49-16-2406 3/4" ProPEX® Expansion Head: 49-16-2408 1" ProPEX® Expansion Head



### M12™ FORCE LOGIC™ **Press Tool Kit**

2473-22 (2473-20 No Jaw Kit)

#### Specifications:

Capacity	1/2" - 1-1/4" CU
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Length / Weight	12.8" / 3.8 lbs

**Includes: 2473-22** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) Jaws (1/2", 3/4", 1"), Charger, Carrying Case; 2473-20 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case (No Jaws Included)

#### **Related Accessories:**

49-16-2450 1/2" CTS Jaw; **49-16-2451** 3/4" CTS Jaw;

49-16-2452 1" CTS Jaw: 49-16-2453 1-1/4" CTS Jaw

49-16-2450B 1/2" IPS Jaw; 49-16-2451B 3/4" IPS Jaw:

49-16-2451C 1/2" PEX Crimp (F1807 & F2159) Jaw;

49-16-2453C 3/4" PEX Crimp (F1807 & F2159) Jaw; 49-16-2454C 1" PEX Crimp (F1807 & F2159) Jaw;

49-16-2455C 1-1/4" PEX Crimp (F1807) Jaw;

49-16-2456C 1-1/2" PEX Crimp (F1807) Jaw



### M12™ No-Hub Driver Kit

2455-22 (2455-20 Tool-Only)

## Specifications

specifications:	
Torque Settings (3-Mode)	60 in-lbs / 80 in-lbs / Drill
RPM	0 – 750
Chuck Type	1/4" Hex
Calibration Interval	25,000 Cycles (LED Indicator)
Weight	2.7 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, (3) SHOCKWAVE™ Nut Drivers (1/4", 5/16", 3/8"), Charger, Carrying Case