

# SAFETY CANS



## TYPE I SAFETY CANS

FLAMMABLES	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4S</b>	<b>UI10S</b>	<b>UI20S</b>	<b>UI25S*</b>	<b>UI50S</b>
<b>Model-w/Funnel</b>	<b>UI4FS</b>	<b>UI10FS</b>	<b>UI20FS</b>	<b>UI25FS*</b>	<b>UI50FS</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5⅝ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9⅞ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13⅞ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>


## TYPE I SAFETY CANS

DIESEL	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SY</b>	<b>UI10SY</b>	<b>UI20SY</b>	<b>UI25SY*</b>	<b>UI50SY</b>
<b>Model-w/Funnel</b>	<b>UI4FSY</b>	<b>UI10FSY</b>	<b>UI20FSY</b>	<b>UI25FSY*</b>	<b>UI50FSY</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5⅝ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9⅞ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13⅞ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

### Type I Safety Cans

- Eagle Type 1 Safety Cans are constructed of 24-gauge hot dipped galvanized steel, whereas other manufacturers' safety cans use lead-coated terne steel
- These safety cans are accepted under CARB, meet OSHA and NFPA Code 30 requirements, and are UL, ULC and FM Approved for safe handling and storage of gasoline and other flammable liquids
- Available in a variety of colors for the safe handling and storage of kerosene (blue), diesel (yellow) and combustible liquids such as oils (green)

\* Meets the New York City Fire Code Title 29 FC 2204.4.4.1.1 Maximum 2.5 gallon (9.5 L) container regulations  
Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



## TYPE I SAFETY CANS

KEROSENE	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SB</b>	<b>UI10SB</b>	<b>UI20SB</b>	<b>UI25SB*</b>	<b>UI50SB</b>
<b>Model-w/Funnel</b>	<b>UI4FSB</b>	<b>UI10FSB</b>	<b>UI20FSB</b>	<b>UI25FSB*</b>	<b>UI50FSB</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5⅝ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9⅞ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13⅞ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

## TYPE I SAFETY CANS

COMBUSTIBLES	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SG</b>	<b>UI10SG</b>	<b>UI20SG</b>	<b>UI25SG*</b>	<b>UI50SG</b>
<b>Model-w/Funnel</b>	<b>UI4FSG</b>	<b>UI10FSG</b>	<b>UI20FSG</b>	<b>UI25FSG*</b>	<b>UI50FSG</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5⅝ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9⅞ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13⅞ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

## TYPE I POLY CANS

TYPE I POLY CANS	TYPE I POLY CANS						TYPE I STAINLESS STEEL CANS	
<b>Model Numbers</b>	<b>14169</b>	<b>14545</b>	<b>14261</b>	<b>14561</b>	<b>14535</b>	<b>14540</b>	<b>1313</b>	<b>1315</b>
<b>Capacity</b>	1 gal./4 L	5 gal./19 L	2.5 gal./9.5 L	5 gal./19 L	5 gal./19 L	5 gal./19 L	2½ gal./9.5 L	5 gal./19 L
<b>Dimensions</b> <small>Diameter Height</small>	7¼ in./184 mm. 11½ in./292 mm.	11¼ in./292 mm. 17 in./432 mm.	10¼ in./273 mm. 14¼ in./362 mm.	12¼ in./324 mm. 16 in./406 mm.	11½ in./292 mm. 17 in./432 mm.	11½ in./292 mm. 17 in./432 mm.	11¼ in./28.6 cm. 9⅞ in./24.5 cm.	11¼ in./28.6 cm. 15⅞ in./39.7 cm.
<b>Weight</b>	3 lbs./1 kg.	10 lbs./4 kg.	4 lbs./2 kg.	9 lbs./4 kg.	16 lbs./7 kg.	10 lbs./4 kg.	8 lbs./3.7 kg.	10 lbs./4.6 kg.
<b>Construction</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Stainless</b>	<b>Stainless</b>