

Mini-Router Pro®

Folding handle





The handle is tall enough to make it easy to roll to the job, yet it can be quickly folded to take up less room in your truck.



J-Drum

With a J-Drum (optional), you're ready for small drain work in seconds. Equipped with a Quick Grip™ chuck with tightening handle. Will hold any Super-Vee cable. **Catalog Number MR-250**

Mini-Router Pro Cutter Set – Catalog # MRCS

Cutter Name	Part Number	Application
 Arrow Head	AH	Starting Drill (Gets water flowing)
 1-1/2" U-Cutter	1-1/2UC	For cutting and scraping
 2" Side Cutter Blades	2SCB	For cutting and scraping
 Boring Gimlet	BG	For removing loose objects



Removable Drum

You can take the drum off the Mini-Router Pro in seconds.

Built-in Dolly

Six inch semi-pneumatic wheels roll easily over rough terrain to and from the job.



Mini-Router Pro™ Units

MRP

Basic Unit: MR-200 Drum, 1/3 hp motor w/Reverse Switch, 10 ft. Power Cord w/GFCI, Water-Proof Air Foot Switch, Leather Gloves.

MRP-J

Basic Unit: Same as above, but with MR-250 J-Drum instead of MR-200 Drum.

MRP-A

Basic Unit, plus 50EM2 (50 ft. x 3/8") Cable, MRCS Cutter Set.

MRP-B

Basic Unit, plus 75EM2 (75 ft. x 3/8") Cable, MRCS Cutter Set.

MRP-C

Basic Unit, plus 50EM3 (50 ft. x 1/2") Cable, MRCS Cutter Set.

MRP-D

Basic Unit, plus 75EM3 (75 ft. x 1/2") Cable, MRCS Cutter Set.

Specifications:

Weight: 43 lbs. (19.5 kg) without cable.

Dimensions: 20" D x 16" W x 38" H (20" H with handle folded) (51 cm x 41 cm x 96 cm - 51 cm)

Drum: Capacity of 75 ft. x 3/8" or 1/2" Flexicore cable. Integral distributor tube. Quickly removable from frame.

J-Drum: Capacity of 50 ft. of 1/4" or 5/16" Flexicore cable.

Wheels: 6" semi-pneumatic tires.

Folding Handle: Reduces storage space.

Cutter Set: MRCS Cutter Set consists of Arrow head, Boring Gimlet, 1-1/2 U-Cutter, 2" Side Cutter Blades. Other cutters available.

Motor: 1/3 hp, with forward-off-reverse switch, spring-loaded mounting for proper belt tension.

Load Speed: 165 rpm.

Belt Guard: High impact plastic.

Power Cable Feed: (Optional) Drives 3/8" and 1/2" cables. For smoother performance, switch to the XP drum with inner drum cage.

Foot Pedal: Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord: 10 ft. 3-wire vinyl covered with molded plug. In-line ground fault circuit interrupter.

Leather Gloves: With double-reinforced palm, for hand protection when guiding cable.



General / **General Wire Spring Co.**
PIPE CLEANERS
 1101 Thompson Avenue • McKees Rocks, PA 15136 USA
 800-245-6200 or 412-771-6300 • Fax: 412-771-2771
 www.drainbrain.com • e-mail: info@drainbrain.com

The toughest tools down the line.™