


General Information

- Manufactured in accordance with all applicable parts of AWWA Standard C-800.
- Castings are made of ASTM B584 Low Lead.
- Every copper meter yoke is pressurized with air to assure there is no leakage.
- Styles include horizontal inlet and outlet, vertical inlet and outlet, straight line, corner type, basement type, meter relocater, tandem, and setters for 5/8" thru 2" meters.
- All styles are available with either integral M.I.P, integral F.I.P. or integral multi-purpose thread ends.
- Meter saddle nuts are regularly furnished to speed installation or removal of the meter.
- Copper meter yoke options include lockwing Ball Angle Meter Valve, lockwing ground key angle meter valves, ASSE approved dual check valves, dual check valves (ASSE non-approved), top entry check valves, test valve and a wide selection of end connections.


**All service brass will comply with AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.*



Copper meter yoke optional fittings



**Lockwing
Ball Angle
Meter Valve**




**Lockwing
Ground Key
Angle Meter Valve**



Test valve



**Top Entry Dual
Check Valve**
(Dual Angle Check also available;
not shown)



**Meter Yoke
Connections**

SECTION 6 – Meter Setters and Resetters

JONES®

a MUELLER brand

Meter Setter Codes and Descriptions

Base Options	
Code	Description
Jo2	Horizontal Bar Meter Yoke & Meter Setters
Jo3	Horizontal Meter Resetter (MT&MT Only)
Jo4	Vertical Bar Meter Setter
Jo5	Vertical Inlet x Horizontal Outlet Meter Yoke
Jo6	Horizontal Inlet x Vertical Outlet Meter Yoke
Jo7	Offset Relocator
Base Inlets & Outlets	
Code	Description
CPS	Pack Joint Connection (IPS PE*)
CTS	Pack Joint Connection (CTS)
FC	Copper Flare
FIP	Female Iron Pipe
MIP	Male Iron Pipe
MT	Male Meter Thread
SG	110 Compression Connection (CTS) (Super Grip)
UN	Multi-Purpose Thread
Meter Inlet Options	
Code	Description
AM	Ground Key Angle Meter Valve
BV	Angle Ball Valve - Full Port
MC	Meter Coupling
RB	Angle Ball Valve - Reduced Port
Meter Outlet Options	
Code	Description
A2	Angle Dual Meter Check Valve - Non-ASSE
AM	Ground Key Angle Meter Valve
BV	Angle Ball Valve - Full Port
DC	Top Entry Angle Dual Check Valve - ASSE
FE	Flange Elbow (1-1/2" & 2" Setters)
MC	Meter Coupling - Standard
RB	Angle Ball Valve - Reduced Port
SC	Angle Meter Single Check Valve - Non-ASSE
Meter Yoke Size	
Code	Description
X	5/8" Meter
A	5/8" x 3/4" Meter
B	3/4" Meter
C	1" Meter
E	1-1/2" Meter
F	2" Meter

SECTION 6 – Meter Setters and Resetters

How to specify a James Jones Setter/Resetter

Example:

E02 A CTS UN – BV DC 12 – –

E NUMBER	METER SIZE	INLET BASE	OUTLET BASE	INLET METER	OUTLET METER	HEIGHT/ Inches	OPTIONS
							– –

E01 = Bracket Only - No Base

E02 = Eye Base "IN "OUT

E03 = Resetter Base - MT x MT

E04 = Base #IN \$OUT

E05 = Base #IN "OUT

E06 = Base "IN \$OUT

E07 = Special resetter
- NO height increase

CPS = Compression Pipe Size

CTS = Compression Copper Tube Size

FIP = Female Iron Pipe

FC = Flared Copper

MT = Meter Thread

MIP = Male Iron Pipe

UN = Universal (FC or FIP)

SDR = Solder

SG = Super Grip Tube Size

SGP = Super Grip Pipe Size

SC = Single Check

DC = ASSE Dual Check

BV = Full Port Ball Valve

RB = Reduced Port Ball Valve

AM = Angle Meter Stop

MC = Meter Coupling

A2 = Angle Dual Check (Non ASSE)

S1 =Straight Single Check

S2 =Straight Dual Check (Non ASSE)

For future use

BK = Base Check

X = 5/8"

A = 5/8" x 3/4"

B = 3/4"

C = 1"

E = 1-1/2"

F = 2"

BV = Full Port Ball Valve

RB = Reduced Port Ball Valve

AM = Angle Meter

MC = Meter Coupling

**Indicate Height
in Inches**

SO# _____ **Customer Name** _____

PO# _____ **Billing Address** _____

Shipping Address _____

Quantity _____ **Selling Price Each: \$** _____

Taken By: _____


JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Resetters


JONES®

a MUELLER brand


Horizontal Bar Meter Yokes (James Jones SuperGrip is Now Known as Jones® 110 Compression Connection)




Eo2-UN-UN-MC-MC



Eo2-UN-UN-AM-MC




Eo2-UN-UN-BV-MC




Eo2-MIP-MIP-MC-MC


Part Number	Description	Size
Eo2-UN-UN-MC-MC	Meter Coupling - both ends Multi-purpose thread (less end connection) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-UN-UN-AM-MC	Lockwing ground key meter valve x meter coupling Multi-purpose thread (less end connection) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-UN-UN-BV-MC	Lockwing ball meter valve x meter coupling Multi-purpose thread (less end connection) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-MIP-MIP-MC-MC	Meter coupling - both ends M.I.P threads on the meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"




E02-MIP-MIP-AM-MC



E02-MIP-MIP-BV-MC



E02-SG-MIP-MC-MC




E02-SG-MIP-AM-MC

Part Number	Description	Size
Eo2-MIP-MIP-AM-MC	Lockwing ground key meter valve x meter coupling M.I.P threads on the meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-MIP-MIP-BV-MC	Lockwing ball meter valve x meter coupling M.I.P threads on the meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-MIP-MC-MC	Meter coupling - both ends Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-MIP-AM-MC	Lockwing ground key meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


Horizontal Bar Meter Yokes cont. (James Jones SuperGrip is Now Known as Jones[®] 110 Compression Connection)




Eo2-SG-MIP-BV-MC



Eo2-SG-FIP-MC-MC




Eo2-SG-FIP-AM-MC




Eo2-SG-FIP-BV-MC


Part Number	Description	Size
Eo2-SG-MIP-BV-MC	Lockwing ball meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-FIP-MC-MC	Meter coupling - both ends Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & F.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-FIP-AM-MC	Lockwing ground key meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & F.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-FIP-BV-MC	Lockwing ball meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS plastic tubing) on meter bar inlet & F.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"



Eo2-CTS-MIP-MC-MC



Eo2-CTS-MIP-AM-MC



Eo2-CTS-MIP-BV-MC



Eo2-SG-SG-MC-MC

Part Number	Description	Size
Eo2-CTS-MIP-MC-MC	Meter coupling x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-CTS-MIP-AM-MC	Lockwing ground key meter valve x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-CTS-MIP-BV-MC	Lockwing ball meter valve x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & M.I.P outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-SG-MC-MC	Meter coupling - both ends Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or plastic tubing CTS) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


SECTION 6 – Meter Setters and Resetters

JONES®


a MUELLER brand

Horizontal Bar Meter Yokes


(James Jones SuperGrip is Now Known as Jones® 110 Compression Connection)




Eo2-SG-SG-AM-MC



Eo2-SG-SG-BV-MC




Eo2-SG-SG-MC-MC-AC




Eo2-SG-SG-AM-MC-AC


Part Number	Description	Size
Eo2-SG-SG-AM-MC	Lockwing ground key meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-SG-BV-MC	Lockwing ball meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or PE plastic tubing CTS) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-SG-MC-MC-AC	Meter coupling - both ends - for 5/8", 5/8" x 3/4" & 3/4" meters with 1" integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or PE plastic tubing CTS) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-SG-AM-MC-AC	Lockwing ground key meter valve x meter coupling for 5/8", 5/8" x 3/4" & 3/4" meters with 1" integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or PE plastic tubing CTS) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"




Eo2-SG-SG-BV-MC-AC



Eo2-CTS-CTS-MC-MC



Eo2-CTS-CTS-AM-MC




Eo2-CTS-CTS-BV-MC


Part Number	Description	Size
Eo2-SG-SG-BV-MC-AC	Lockwing ball meter valve x meter coupling - for 5/8", 5/8" x 3/4" & 3/4" meters with 1" integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or PE plastic tubing CTS) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-CTS-CTS-MC-MC	Meter coupling - both ends Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-CTS-CTS-AM-MC	Lockwing ground key meter valve x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
Eo2-CTS-CTS-BV-MC	Lockwing ball meter valve x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


Horizontal Bar Meter Yokes




E02-CTS-CTS-MC-MC-AC



E02-CTS-CTS-AM-MC-AC




E02-CTS-CTS-BV-MC-AC




E02-CPS-CPS-MC-MC


Part Number	Description	Size
E02-CTS-CTS-MC-MC-AC	Meter coupling - both ends - for 5/8", 5/8" x 3/4" & 3/4" meters with 1" integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4"
E02-CTS-CTS-AM-MC-AC	Lockwing ground key meter valve x meter coupling - for 5/8", 5/8" x 3/4" & 3/4" meters with 1" Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4"
E02-CTS-CTS-BV-MC-AC	Lockwing ball meter valve x meter coupling - for 5/8", 5/8" x 3/4" & 3/4" meters with 1" Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4"
E02-CPS-CPS-MC-MC	Meter coupling - both ends Integral pack joint connection (for IPS PE pipe) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"




E02-CPS-CPS-AM-MC



E02-CPS-CPS-BV-MC



E02-FC-FC-MC-MC



E02-FC-FC-AM-MC

Part Number	Description	Size
E02-CPS-CPS-AM-MC	Lockwing ground key meter valve x meter coupling Integral pack joint connection (for IPS PE pipe) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
E02-CPS-CPS-BV-MC	Lockwing ball meter valve x meter coupling Integral pack joint connection (for IPS PE pipe) on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
E02-FC-FC-MC-MC	Meter coupling - both ends Integral copper flare on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"
E02-FC-FC-AM-MC	Lockwing ground key meter valve x meter coupling Integral copper flare on meter bar inlet & outlet	5/8" 5/8"x3/4" 3/4" 1"


JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Reseters

JONES®

a MUELLER brand


Horizontal Bar Meter Yokes (James Jones SuperGrip is Now Known as Jones® 110 Compression Connection)




Eo2-FC-FC-BV-MC



Eo2-SG-UN-MC-MC



Eo2-SG-UN-AM-MC




Eo2-SG-UN-BV-MC


Part Number	Description	Size
Eo2-FC-FC-BV-MC	Lockwing ball meter valve x meter coupling Integral copper flare on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-UN-MC-MC	Meter coupling - both ends Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-UN-AM-MC	Lockwing ground key meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo2-SG-UN-BV-MC	Lockwing ball meter valve x meter coupling Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4" 1"




Eo2-SG-UN-MC-MC-AC



Eo2-SG-UN-AM-MC-AC



Eo2-SG-UN-BV-MC-AC




Eo2-CTS-UN-MC-MC


Part Number	Description	Size
Eo2-SG-UN-MC-MC-AC	Meter coupling - both ends 1" Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4"
Eo2-SG-UN-AM-MC-AC	Lockwing ground key meter valve x meter coupling 1" Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4"
Eo2-SG-UN-BV-MC-AC	Lockwing ball meter valve x meter coupling 1" Integral 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4"
Eo2-CTS-UN-MC-MC	Meter coupling - both ends Integral pack joint connection (for copper or CTS plastic tubing) on inlet. Multi-purpose thread (less end connection) on outlet.	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

Horizontal Bar Meter Yokes




E02-CTS-UN-AM-MC



E02-CTS-UN-BV-MC




E02-CTS-UN-MC-MC-AC



E02-CTS-UN-AM-MC-AC

Part Number	Description	Size
E02-CTS-UN-AM-MC	Lockwing ground key meter valve x meter coupling Integral pack joint connection (for copper or pe plastic tubing cts) on inlet. Multi-purpose thread (less end connection) on outlet	5/8" 5/8"x3/4" 3/4" 1"
E02-CTS-UN-BV-MC	Lockwing ball meter valve x meter coupling. Integral pack joint connection (for copper or pe plastic tubing cts) on inlet. Multi-purpose thread (less end connection) on outlet	5/8" 5/8"x3/4" 3/4" 1"
E02-CTS-UN-MC-MC-AC	Meter coupling - both ends 1" Integral pack joint connection (for copper or pe plastic tubing cts) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet	5/8" 5/8"x3/4" 3/4"
E02-CTS-UN-AM-MC-AC	Lockwing ground key meter valve x meter coupling 1" Integral pack joint connection (for copper or pe plastic tubing cts) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet	5/8" 5/8"x3/4" 3/4"



E02-CTS-UN-BV-MC-AC

Part Number	Description	Size
E02-CTS-UN-BV-MC-AC	Lockwing ball meter valve x meter coupling 1" Integral pack joint connection (for copper or pe plastic tubing cts) on inlet. 3/4" Multi-purpose thread (less end connection) on outlet	5/8" 5/8"x3/4" 3/4"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Resetters


JONES®

a MUELLER brand


Vertical Inlet x Horizontal Outlet Meter Yokes (James Jones SuperGrip is Now Known as Jones® 110 Compression Connection)




Eo5-SG-UN-MC-MC



Eo5-SG-UN-AM-MC




Eo5-SG-UN-BV-MC




Eo5-MIP-UN-MC-MC


Part Number	Description	Size
Eo5-SG-UN-MC-MC	Meter coupling - both ends Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-SG-UN-AM-MC	Lockwing ground key meter valve x meter coupling. Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-SG-UN-BV-MC	Lockwing ball meter valve x meter coupling. Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-MIP-UN-MC-MC	Meter coupling - both ends MIP threads on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"




Eo5-MIP-UN-AM-MC



Eo5-MIP-UN-BV-MC



Eo5-CTS-UN-MC-MC




Eo5-CTS-UN-AM-MC


Part Number	Description	Size
Eo5-MIP-UN-AM-MC	Lockwing ground key meter valve x meter coupling MIP threads on vertical bar inlet Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-MIP-UN-BV-MC	Lockwing ball meter valve x meter coupling. MIP threads on vertical bar inlet Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-CTS-UN-MC-MC	Meter coupling - both ends Integral pack joint connection (for copper or CTS plastic tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo5-CTS-UN-AM-MC	Lockwing ground key meter valve x meter coupling Integral pack joint connection (for copper or CTS plastic tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


Vertical Inlet x Horizontal Outlet Meter Yokes cont.




E05-CTS-UN-BV-MC



E05-FC-UN-MC-MC




E05-FC-UN-AM-MC




E05-FC-UN-BV-MC

Part Number	Description	Size
E05-CTS-UN-BV-MC	Meter coupling - both ends Integral pack joint connection (for copper or CTS plastic tubing) on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
E05-FC-UN-MC-MC	Meter coupling - both ends Integral copper flare connection on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
E05-FC-UN-AM-MC	Lockwing ground key valve x meter coupling. Integral copper flare connection on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"
E05-FC-UN-BV-MC	Lockwing ball meter valve x meter coupling. Integral copper flare connection on vertical bar inlet. Multi-purpose thread (less end connection) on horizontal bar outlet.	5/8" 5/8"x3/4" 3/4" 1"


Vertical Bar Meter Yokes



E04-UN-UN-MC-MC



E04-UN-UN-AM-MC



E04-UN-UN-BV-MC

Part Number	Description	Size
E04-UN-UN-MC-MC (less meter valve)	Meter coupling - both ends Multi-purpose thread (less end connection) meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E-04-UN-UN-AM-MC (Ground Key Meter Valve)	Lockwing ground key meter valve x meter coupling. Multi-purpose thread (less end connection) meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E04-UN-UN-BV-MC	Lockwing ball meter valve x meter coupling. Multi-purpose thread (less end connection) meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


SECTION 6 – Meter Setters and Resetters

JONES®


a MUELLER brand

Vertical Bar Meter Yokes


(James Jones SuperGrip is Now Known as Jones® 110 Compression Connection)



Eo4-SG-SG-MC-MC



Eo4-SG-SG-AM-MC




Eo4-SG-SG-BV-MC


Part Number	Description	Size
Eo4-SG-SG-MC-MC (less meter valve)	Meter coupling - both ends Integral Jones® 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-SG-SG-AM-MC (Ground Key Meter Valve)	Lockwing ground key valve x meter coupling. Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-SG-SG-BV-MC	Lockwing ball meter valve x meter coupling. Integral Jones 110 compression connection (Super Grip) (for soft/annealed copper or CTS PE tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"



Eo4-CTS-CTS-MC-MC



Eo4-CTS-CTS-AM-MC




Eo4-CTS-CTS-BV-MC

Part Number	Description	Size
Eo4-CTS-CTS-MC-MC (less meter valve)	Meter coupling - both ends. Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-CTS-CTS-AM-MC (Ground Key Meter Valve)	Lockwing ground key meter valve x meter coupling. Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-CTS-CTS-BV-MC	Lockwing ball meter valve x meter coupling. Integral pack joint connection (for copper or CTS plastic tubing) on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

Vertical Bar Meter Yokes cont.



Eo4-FC-FC-MC-MC




Eo4-FC-FC-AM-MC




Eo4-FC-FC-BV-MC


Part Number	Description	Size
Eo4-FC-FC-MC-MC (less meter valve)	Meter coupling - both ends. Integral copper flare on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-FC-FC-AM-MC (Ground Key Meter Valve)	Lockwing ground key meter valve x meter coupling. Integral copper flare on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-FC-FC-BV-MC	Lockwing ball meter valve x meter coupling. Integral copper flare on meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"



Eo4-MIP-MIP-MC-MC



Eo4-MIP-MIP-AM-MC



Eo4-MIP-MIP-BV-MC

Part Number	Description	Size
Eo4-MIP-MIP-MC-MC (less meter valve)	Meter coupling - both ends. MIP threads on the meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-MIP-MIP-AM-MC (Ground Key Meter Valve)	Lockwing ground key meter valve x meter coupling. MIP threads on the meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
Eo4-MIP-MIP-BV-MC	Lockwing ball meter valve x meter coupling. MIP threads on the meter bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"


JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Resetters


JONES®

a MUELLER brand


Large Horizontal Meter Setters



Eo2-FIP-FIP-BV-FE




Eo2-FIP-FIP-BV-AZ




Eo2-FIP-FIP-BV-BV


Part Number	Description	Size
Eo2-FIP-FIP-BV-FE	Lockwing ball meter valve with meter flange x meter coupling. FIP service line horizontal inlet & outlet.	1-1/2" 2"
Eo2-FIP-FIP-BV-AZ	Lockwing ball meter valve with meter flange x flanged angle dual check valve. FIP service line horizontal inlet & outlet.	1-1/2" 2"
Eo2-FIP-FIP-BV-BV	Lockwing ball meter valve with meter flange x lockwing ball meter valve with meter flange. FIP service line horizontal inlet & outlet.	1-1/2" 2"




Eo2-FIP-FIP-BV-BV-AR



Eo2-FIP-FIP-BV-SC-AR



Eo2-FIP-FIP-BV-BV-AS




Eo2-FIP-FIP-BV-AZ-AS


Part Number	Description	Size
Eo2-FIP-FIP-BV-BV-AR	Lockwing ball meter valve with meter flange x lockwing ball meter valve with meter flange. FIP service line horizontal inlet & outlet.	1-1/2" 2"
Eo2-FIP-FIP-BV-AZ-AR	Lockwing ball meter valve with meter flange x dual check valve with meter flange. Check valve is in front of the by-pass valve. FIP service line horizontal inlet & outlet.	1-1/2" 2"
Eo2-FIP-FIP-BV-BV-AS	Lockwing ball meter valve x lockwing ball meter valve with meter flange. Elevated by-pass. FIP service line horizontal inlet & outlet.	1-1/2" 2"
Eo2-FIP-FIP-BV-AZ-AS	Lockwing ball meter valve with meter flange x dual check valve with meter flange. Check valve is on the outlet side of the meter, underneath the meter valve. Elevated by-pass. FIP with high by-pass service line horizontal inlet & outlet.	1-1/2" 2"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

Horizontal Meter Resetters



E03-MT-MT-MC-MC




E03-MT-MT-AM-MC




E03-MT-MT-BV-MC


Part Number	Description	Size
E03-MT-MT-MC-MC	Meter coupling x meter coupling MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E03-MT-MT-AM-MC	Lockwing ground key meter x meter coupling MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E03-MT-MT-BV-MC	Lockwing ball meter valve x meter coupling MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"



E07-MT-MT-MC-MC



E07-MT-MT-AM-MC



E07-MT-MT-BV-MC

Part Number	Description	Size
E07-MT-MT-MC-MC (less meter valve)	Meter coupling - both ends MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E07-MT-MT-AM-MC (Ground Key Meter Valve)	Lockwing ground key meter valve x meter coupling MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"
E07-MT-MT-BV-MC	Lockwing ball meter x meter coupling MIP meter thread bar inlet & outlet.	5/8" 5/8"x3/4" 3/4" 1"

*Offset right is standard. Offset left is available upon request.


JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Resetters


JONES®

a MUELLER brand


Large Meter Resetters



E03-FL-FL-BV-FE




E03-FL-FL-BV-AZ




E03-FL-FL-BV-BV

Part Number	Description	Size
E03-FL-FL-BV-FE	Lockwing ball meter valve with meter flange x meter coupling Meter flange service line inlet & outlet	1-1/2" 2"
E03-FL-FL-BV-AZ	Lockwing ball meter valve with meter flange x flanged angel dual check valve Meter flange service line inlet & outlet	1-1/2" 2"
E03-FL-FL-BV-BV	Lockwing ball meter valve with meter flange x lockwing ball meter valve with meter flange Meter flange service line inlet & outlet	1-1/2" 2"

Large Meter Resetters With By-Pass



E03-FL-FL-BV-BV-AR




E03-FL-FL-BV-AZ-AR


Part Number	Description	Size
E03-FL-FL-BV-BV-AR	Lockwing ball meter valve with meter flange x lockwing ball meter valve with meter flange Meter flange service line inlet & outlet	2"
E03-FL-FL-BV-AZ-AR	Lockwing ball meter valve with meter flange x dual check valve with meter flange Meter flange service line inlet & outlet	2"

JONES Meter Setters are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.


End Connections for Copper Meter Yokes with Multi-Purpose Ends




H-14227N




P-14227N



H-14228N



H-14230N



E-14228N


Part Number	Description	Size			
		Category size	Meter size	Tubing size	
H-14227N	Straight coupling. Multi-purpose thread x Jones® 110 Conductive Compression (Super Grip) Connection for CTS O.D. tubing	5/8" x 3/4" x 3/4"	5/8" x 3/4" x 1"	1"	
		5/8", 5/8" x 3/4", 3/4"	5/8", 5/8" x 3/4", 1"	1"	
		3/4"	1"	1"	
P-14227N	Straight coupling. Multi-purpose thread x Pack Joint Connection for CTS O.D. tubing	5/8" x 3/4" x 3/4"		1"	
		5/8", 5/8" x 3/4", 3/4"		1"	
		3/4"		1"	
H-14228N	Straight coupling. Multi-purpose thread x Jones 110 Compression Connection (Super Grip) for IPS PE pipe	5/8" x 3/4" x 3/4"		1"	
		5/8", 5/8" x 3/4", 3/4"		1"	
		3/4"		1"	
H-14230N	Straight coupling. Multi-purpose thread x INSTA-TITE® Connection for CTS O.D. PE tubing	5/8" x 3/4" x 3/4"		1"	
		5/8", 5/8" x 3/4", 3/4"		1"	
		3/4"		1"	
E-14228N	Straight coupling. Multi-purpose thread x Pack Joint Connection for IPS PE pipe	5/8" x 3/4" x 3/4"			
		5/8", 5/8" x 3/4", 3/4"			
		3/4"			



507310N / 507311N



H-14222N



H-14221N



H-14224N

Part Number	Description	Size		
		Part Number	Category size	Meter size
507310N / 507311N	Straight coupling. F.I.P x male multi-purpose thread Used to adapt M.I.P. yokes to multi-purpose couplings	507310	3/4"	1"
			5/8", 5/8" x 3/4", 3/4"	1"
			3/4"	1"
H-14222N	Straight coupling. Multi-purpose thread x copper flare or F.I.P.	5/8" x 3/4" x 3/4"		1"
		5/8", 5/8" x 3/4", 3/4"		1"
		3/4"		1"
H-14221N	Straight coupling. Multi-purpose thread x compression connection with plain gasket and locking type nut for steel pipe	5/8" x 3/4" x 3/4"		
		5/8", 5/8" x 3/4", 3/4"		
		3/4"		
H-14224N	Straight coupling. Multi-purpose thread x copper flare nut	5/8" x 3/4" x 3/4"		1"
		5/8", 5/8" x 3/4", 3/4"		1"
		3/4"		1"


JONES Connections are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

SECTION 6 – Meter Setters and Resetters


JONES®

a MUELLER brand


End Connections for Copper Meter Yokes with Multi-Purpose Ends cont.



H-14220N



H-14223N



H-14231N



H-14211N

Part Number	Description	Size			
		Category size	Meter size	Tubing size	
H-14220N	Straight coupling. Multi-purpose thread x compression connection with plain gasket for steel pipe	Category size	5/8" x 3/4" x 3/4"		
		Meter size	5/8", 5/8" x 3/4", 3/4"		
		Tubing size	3/4"		
H-14223N	Straight coupling. Multi-purpose thread x copper flare or M.I.P. thread	Category size	5/8" x 3/4" x 3/4"	5/8" x 3/4" x 1"	1"
		Meter size	5/8", 5/8" x 3/4", 3/4"	-	1"
		Tubing size	3/4"	1"	1"
H-14231N	Straight coupling. Multi-purpose thread x sweat-joint solder connection	Category size	5/8" x 3/4" x 3/4"	5/8" x 3/4" x 1"	1"
		Meter size	5/8", 5/8" x 3/4", 3/4"	-	1"
		Tubing size	3/4"	1"	1"
H-14211N	Straight coupling F.I.P. spud x F.I.P. thread tail piece union	Category size	3/4"	1"	
		Meter size	3/4"	1"	
		Tubing size	1"	1"	

JONES Connections are manufactured and tested in accordance with ANSI/AWWA C-800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.

Equipment and Tools



Brass Hammer

Solid brass head with
10" wooden handle.
Weight 2-3/4 lb.

CATALOG NUMBER: **J-18025**



Copper flare nut

CATALOG NUMBER: **J-15430**

1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	----	--------	--------	----



Brass cap

Fits on copper
flare spud to cap off line.

CATALOG NUMBER: **J-15540N**

3/4"	1"
------	----



Solid copper disc

Used with regular
copper flare nut to shut off line.

CATALOG NUMBER: **J-15535**

1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	----	--------	--------	----



Flaring tool

Used to make 45° flare on
type "K" copper tubing.

CATALOG NUMBER: **J-18000**

1/2"	5/8"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	------	----	--------	--------	----



Drilled flaring tool

Used to make 45° flare on type "K" copper
tubing without shutting off water-drilled
to exhaust water at right angle to tubing.

CATALOG NUMBER: **J-18005**

3/4"	1"
------	----



Reamer

Used to ream the inside of type
"K" copper tubing to remove
burrs prior to flaring.

CATALOG NUMBER: **J-18010**

1/2"	3/4"	1"
------	------	----

Note: When using any striking tool, safety eye protection must be worn. Inspect hammer and tools for any damage after each use and repair or replace if mushrooming or chipping is evident.

JONES[®]

a **MUELLER** brand

www.jamesjones.com