


Ductless Mini-Split System Single Phase – 1½-3 Tons




4TXK85



4MXW85

Table DU-1-A — 18 SEER R-410A Mini-Split System HP — Single Phase, 1/2 to 3 Ton^①

Outdoor Model Number Indoor Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			W	D	H					OD Gas	OD Liq.
4TXK8509A10N0B	208/230/1/60	9,000	33.4	12.6	21.3	90.3	60	10	15	3/8	1/4
4MXW8509A10N0B	208/230/1/60		33.3	7.1	10.8	28.6	42-52			3/8	1/4
4TXK8512A10N0B	208/230/1/60	12,000	33.4	12.6	23.2	96.9	62	10	15	3/8	1/4
4MXW8512A10N0B	208/230/1/60		33.3	7.1	10.8	28.6	43-54			3/8	1/4
4TXK8518A10N0B	208/230/1/60	18,000	37.6	15.6	27.6	110.1	65	16	20	1/2	1/4
4MXW8518A10N0B	208/230/1/60		37	7.9	11.7	37.4	45-59			1/2	1/4
4TXK8524A10N0B	208/230/1/60	21,400	38.6	16.8	31.1	145.3	68	16	20	5/8	1/4
4MXW8524A10N0B	208/230/1/60		39.6	8.6	12.4	46.2	47-63			5/8	1/4
4TXK8536A10N0B ^②	208/230/1/60	33,600	38.6	16.8	31.1	170	75	23	35	5/8	1/4
4MXW8536A10N0B ^②	208/230/1/60		53.1	10	12.8	59.5	63-69			5/8	1/4




4TXK65



4MXW65

Table DU-1-B — 16 SEER R-410A Mini-Split System HP — Single Phase, 1/2 to 2 Ton^①

Outdoor Model Number Indoor Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			W	D	H					OD Gas	OD Liq.
4TXK6509A10N0B	208/230/1/60	9,000	27.9	12.5	21.7	72.7	59	10	15	3/8	1/4
4MXW6509A10N0B	208/230/1/60		30.3	7.9	11.1	25.3	36-53			3/8	1/4
4TXK6512A10N0B	208/230/1/60	12,000	27.9	12.5	21.7	77.1	62	10	15	3/8	1/4
4MXW6512A10N0B	208/230/1/60		30.3	7.9	11.1	26.4	38-54			3/8	1/4
4TXK6518A10N0B	208/230/1/60	18,000	37.6	15.6	27.6	114.5	66	15	25	1/2	1/4
4MXW6518A10N0B	208/230/1/60		34.1	8.5	12	35.2	43-58			1/2	1/4
4TXK6524A10N0B	208/230/1/60	22,000	37.6	15.6	27.6	125.5	56	16	25	1/2	1/4
4MXW6524A10N0B	208/230/1/60		39.7	8.7	12.4	44	44-59			1/2	1/4



4TYK65



4MYW65

Table DU-1-C — 16 SEER R-410A Mini-Split System AC — Single Phase, 1/2 to 2 Ton^①

Outdoor Model Number Indoor Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			W	D	H					OD Gas	OD Liq.
4TYK6509A10N0B	208/230/1/60	9,000	28	12.5	21.7	72.7	59	10	15	3/8	1/4
4MYW6509A10N0B	208/230/1/60		30.3	7.9	11.1	25.3	36-53			3/8	1/4
4TYK6512A10N0B	208/230/1/60	12,000	28	12.5	21.7	77.1	62	10	15	3/8	1/4
4MYW6512A10N0B	208/230/1/60		30.3	7.9	11.1	26.4	38-54			3/8	1/4
4TYK6518A10N0B	208/230/1/60	18,000	37.6	15.6	27.6	114.5	66	15	25	1/2	1/4
4MYW6518A10N0B	208/230/1/60		34.1	8.5	12	35.2	43-58			1/2	1/4
4TYK6524A10N0B	208/230/1/60	22,000	37.6	15.6	27.6	123.3	66	16	25	1/2	1/4
4MYW6524A10N0B	208/230/1/60		39.7	8.7	12.4	44	44-59			1/2	1/4


① See AHRI for approved combinations and ratings.

② Rated at 16 SEER

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.

Ductless Multi-Split System Single Phase – ½ - 3-½ Tons



4TXM65

Table DU-2-A — R-410A Multi-Split System HP — Single Phase^{①②③}

Outdoor Model Number Indoor Model Number	Power Supply	Nom. Cap. Cooling (BTUH) ^④	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)		No. of Circuits
			W	D	H					OD Gas	OD Liq.	
4TXM6518A1020B	208/230/1/60	18,000	35.4	14.9	23.5	105.6	66	15	20	3/8	1/4	2
4TXM6524A1030B	208/230/1/60	24,000	37.2	15.6	27.6	145.2	66	20	30	3/8	1/4	3
4TXM6530A1040B	208/230/1/60	30,000	37.2	15.6	27.6	147.4	66	26	45	3/8	1/4	4
4TXM6542A1050B	208/230/1/60	42,000	40.0	17.3	43.4	246.4	68	26	40	3/8	1/4	5 ^⑤



4MXW85

Table DU-2-B — 16 SEER R-410A Multi-Split System HP — Single Phase^②

Outdoor Model Number Indoor Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)		No. of Circuits
			W	D	H					OD Gas	OD Liq.	
4MXW8509A10N0B	208/230/1/60	9,000	33.3	7.1	10.8	28.6	42-52			3/8	1/4	
4MXW8512A10N0B	208/230/1/60	12,000	33.3	7.1	10.8	28.6	43-54			3/8	1/4	
4MXW8518A10N0B	208/230/1/60	18,000	37	7.9	11.7	37.4	45-59			1/2	1/4	

① Units are matched with 4MXW85 indoor units.

② See AHRI for allowable combinations and ratings.

③ Because of limited capabilities, please refer to the product ratings for approved combinations.

④ Capacity varies depending on the indoor unit matches.

⑤ Includes two 3/8 x 1/4 circuits, two 1/2 x 1/4 circuits, and one 5/8 x 3/8 circuit.

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.

Ductless Mini-split and Multi Split

Table DU-3-A — Features

	4TXK85 Mini-split HP 18 SEER	4TXK65 Mini-split HP 16 SEER	4TYK65 Mini-split AC 16 SEER	4TXM65 Multi-split 16-22 SEER
• R410-A refrigerant.....	✓	✓	✓	✓
• Flexibility to accommodate to different applications.....	—	—	—	✓
• Connect up to 5 indoor units to a single condensing unit.....	—	—	—	✓
• Nominal capacity 9-24 MBH.....	—	✓	✓	—
• Nominal capacity 9-36 MBH.....	✓	—	—	✓
• Nominal capacity 10-42 MBH.....	—	—	—	✓
• Cooling efficiency 16 SEER.....	—	✓	✓	✓
• Cooling efficiency range 16-22 SEER.....	✓	—	—	—
• Heating efficiency range 8-8.5 HSPF.....	—	✓	✓	✓
• Heating efficiency range 8.2-10 HSPF.....	✓	—	—	—
• Cooling or Heat Pump.....	✓	✓	—	✓
• Cooling only.....	—	—	✓	—
• Low sound level.....	✓	✓	✓	✓
• Blue fin anti-corrosion treatment.....	✓	✓	—	✓
• Energy Star qualified.....	✓	—	—	—
• ETL and AHRI listed.....	✓	✓	✓	✓
• Sleep mode function.....	✓	✓	✓	✓
• Memory reset function.....	✓	✓	✓	✓
• Low ambient cooling to 0 degrees F.....	✓	✓	✓	✓
• Improved air quality with active carbon and catechin filters.....	✓	✓	✓	✓
• Registered limited warranty 5-year on all other functional parts (Residential Use)①	✓	✓	✓	✓
• Optional extended warranties available	✓	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

See the Service First Mini-Split Accessory Catalog for the complete accessory list.

Table DU-3-B — Optional outdoor unit accessories

Model Number	Description	4TXK85 Mini-split HP 18 SEER	4TXK65 Mini-split HP 16 SEER	4TYK65 Mini-split AC 16 SEER	4TXM65 Multi-split 16-22 SEER
TAYREFLN050.....	Lineset Kit 1/4 x 3/8 - 25'	✓	✓	✓	✓
TAYREFLN055.....	Lineset Kit 1/4 x 3/8 - 35'	✓	✓	✓	✓
TAYREFLN060.....	Lineset Kit 1/4 x 3/8 - 50'	✓	✓	✓	✓
TAYREFLN560.....	Lineset Kit 1/4 x 1/2 - 25'	✓	✓	✓	✓
TAYREFLN565.....	Lineset Kit 1/4 x 1/2 - 35'	✓	✓	✓	✓
TAYREFLN570.....	Lineset Kit 1/4 x 1/2 - 50'	✓	✓	✓	✓
TAYREFLN155.....	Lineset Kit 1/4 x 5/8 - 25'	✓	—	—	✓
TAYREFLN160.....	Lineset Kit 1/4 x 5/8 - 35'	✓	—	—	✓
TAYREFLN165.....	Lineset Kit 1/4 x 5/8 - 50'	✓	—	—	✓

Table DU-3-C — Optional indoor unit accessories

Model Number	Description	4TXW85 Mini-split Indoor 18 SEER	4MXW65 Mini-split Indoor 16 SEER	4MYW65 Mini-split Indoor 16 SEER
BAYFTHW01P2A.....	Active Carbon & Catechin filters for 9 & 12 MBH 16 SEER units.....	✓	✓	✓
BAYFTHW02P2A.....	Active Carbon & Catechin filters for 18 & 24 MBH 16 SEER units and9, 12, 18 & 24 MBH 18 SEER units.....	✓	✓	✓
BAYFTHW03P2A.....	Active Carbon & Catechin filters for 36 MBH 18 SEER units.....	✓	✓	✓
AREMOTE1AHAND1.....	Wireless controller.....	✓	✓	✓