



K-101 8" SWING SPOUT SPLASH MOUNT FAUCET

Conforms To NSF 61/9 Lead Free Requirements

Item #: _____ Qty #: _____

Model #: _____

Project #: _____



FAUCET AERATOR CONFORM TO
ASTM.A112.18.1M • 1.5 GPM/5.7 LP
THREAD: 55/64 - 27 FEMALE

FEATURES:

- 8" swing spout.
- 8" O.C. water supply.
- Quarter-turn wedge style handles.
- Colored hot & cold indexes.
- 1.5 GPM/5.7 LPM Aerator. 60 PSI.

MATERIAL:

- Brass chrome plated body & spout.
- Chrome plated handles.



**Click This Link To
View Assembly Sheet**

Options & Accessories

Replacement Spout For K-101 Faucet

8" Swing Spout Only.

K-101SP



Low Flow Aerator

.5 GPM

K-08



Replacement Cartridges*

K-00B (Set of 2)



Splash Mount Faucet Mounting Kit

K-06



Replacement Handles*

K-00C (Set of 2)



Wrist Handles*


K-316-LU (Set of 2)



For a Complete faucet with Wrist
Handles, See our **K-316** Spec Sheet.

*Can Only Be Used On Faucets Purchased After January 2016.
For Older Faucets, Consult Customer Service.

DIMENSIONS and SPECIFICATIONS



| A Length | B Height | C | D | On Center Dimensions |
|-------------|-------------|--------|-----|-------------------------|
| 8" | 4 1/4" | 2 1/4" | 10" | 8" O.C. |

WARNING:

Faucet(s) on this page may expose you to chemicals, including lead, that are known to the State of California to cause cancer or birth defects or other reproductive harm. For more Info., visit www.p65warnings.ca.gov.



Customer Service Available To Assist You **1-800-645-3166** 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933