



**MCR  
SAFETY**

**9674  
UltraTech  
Dipped  
Specification Sheet**

**PRODUCT DESCRIPTION:**

The UltraTech® series provides users with tactile sensitivity, dexterity, and abrasion resistance. This series offers a variety of palm coatings over a durable nylon or poly/cotton shell to fit your needs. The 9674 "UltraTech® Foam" features a 15 gauge 100% nylon shell that has a foam nitrile coated palm. Offers good grip in wet or dry applications. CE score of 3121.

**FEATURES:**

- Excellent comfort and fit
- Excellent grip
- Greater dexterity
- 15 gauge 100% nylon shell
- Foam nitrile coated palm
- CE score of 3121

**APPLICATIONS:**

First responder, Assembly Line Production, Carpentry, Construction, Landscaping, Material Handling, Warehousing

**TECHNICAL DATA FOR: 9674XL**

<b>Series</b>	UltraTech	<b>EN 388 : CE Score - Abrasion</b>	3
<b>Material Group</b>	Strings	<b>EN 388 : CE Score - Cut</b>	1
<b>Product Type</b>	Dipped	<b>EN 388 : CE Score - Tear</b>	3
<b>Glove Size</b>	X - Large	<b>EN 388 : CE Score - Puncture</b>	1
<b>Gauge</b>	15 Gauge	<b>ANSI Puncture</b>	2
<b>Material</b>	Nylon	<b>ANSI Abrasion</b>	4
<b>Made In</b>	China, Malaysia, Pakistan		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2019 MCR Safety - All Rights Reserved



**MCR**  
SAFETY

**9674**  
**UltraTech**  
**Dipped**  
**Specification Sheet**



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9674XS	X - Small	8.66	3.35	2.56	13.344 lb.	1.112
9674M	Medium	9.45	3.54	2.48	16.344 lb.	1.362
9674XL	X - Large	10.43	3.82	2.95	18.456 lb.	1.538
9674S	Small	9.06	3.54	2.76	14.664 lb.	1.222
9674L	Large	9.84	3.94	2.36	18.576 lb.	1.548

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2019 MCR Safety - All Rights Reserved