Product Details Page 1 of 1



Product 47335

Number:

Order LU150/MULTI-KIT

Abbreviation:

General 120/208/240/277V multi-tap magnetic core and coil ballast for 150W high

Description: pressure sodium lamp

Product Information	
Abbrev. With Packaging Info.	LU150MULTIKIT 1/CS 1/SKU
ANSI Code	S55
Ballast Factor	1
Ballast Height H (in)	3.8500
Ballast Length L (in)	3.9400
Ballast Width W (in)	2.8100
Capacitor Diameter	1.4
Capacitor Height	2 45/64"
Circuit Type	HX-HPF
Input Current (Amps)	0.00
Nominal Voltage (V)	120/208/240/277V
Number of Lamps	1
Open Circuit Voltage (V)	120
Power Factor	>0.9
Primary Lamp Type	LU150
Sound Rating	N
Starting Method	PULSE IGNITOR
Starting Temperature - Fahrenheit	-40°F
Starting Temperature - Celsius	-40°C
Total Harmonic Distortion (THD)	<20%
Wiring Method	LEADS
Total Maximum Wattage	188



Footnotes

- Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Install in accordance with National Electric Codes
- High Voltage Pulse Present on Open Circuit
- · Ground Ballast Core and Metallic Case of Capacitor and Ignitor
- Minimum Starting Temperature: -40F/-40C.
- Product contains installation instructions