

# SUBMITTAL INFORMATION






#### TAPPED STAINLESS STEEL SADDLE



Stainless Steel Nuts and Studs - Type 304 stainless steel studs per ASTM A193 and A194. Heavy hex nuts are coated to prevent galling.

Washers - Type 304 stainléss steel per ASTM A193 and A194

Lifter Bars - Type 304 stainless



Gasket - NBR (Buna-N) rubber per ASTM D2000. Optional EPDM available.

Stainless Band - Type 304 stainless steel. Saddles are fully passivated to restore stainless steel characteristics.

Nom. Pipe Size	SADDLE O.D. RANGE (In.)	TAP SIZE 1/2" - 1"				TAP SIZE 1-1/4" - 2"				CATALOG
		BAND WIDTH	No. of Bolts	Bolt Size	APPROX. Wt. Lbs.	BAND WIDTH	No. of Bolts	BOLT SIZE	Approx. Wt. Lbs.	Number
2"	2.13 2.38 2.50-2.70	4"	1	1/2"	1.7	N/A	N/A	N/A	N/A	<ul> <li>♦ FS313-213-TAP</li> <li>♦ FS313-238-TAP</li> <li>♦ FS313-270-TAP</li> </ul>
2-1/2"	2.88	4"	1	1/2"	1.7	N/A	N/A	N/A	N/A	♦ FS313-288-TAP
3"	3.46-3.70 3.50 3.90-4.10	4"	1	1/2"	2	7-1/2"	2	1/2"	3.8	◆* FS313-370-TAP ◆**FS313-350-TAP ◆* FS313-410-TAP
4"	4.50-4.80 4.80-5.20	6"	2	1/2"	2.4	7-1/2"	2	1/2"	4.2	FS313-480-TAP FS313-520-TAP
5"	5.56	6"	2	5/8"	2.7	7-1/2"	2	5/8"	4.8	FS313-556-TAP
6"	6.00-6.40 6.41-6.80 6.63-6.90 6.80-7.20 7.45-7.85	6"	2	5/8"	2.9	7-1/2"	2	5/8"	5.1	FS313-640-TAP FS313-680-TAP FS313-690-TAP FS313-720-TAP FS313-785-TAP
8"	8.00-8.40 8.40-8.80 8.63-9.05 9.00-9.40	6"	2	5/8"	3.3	7-1/2"	2	5/8"	5.6	FS313-840-TAP FS313-880-TAP FS313-905-TAP FS313-940-TAP
10"	10.00-10.40 10.40-10.80 10.75-11.10 11.10-11.50	6"	2	5/8"	6.2	7-1/2"	2	5/8"	6.6	FS313-1040-TAP FS313-1080-TAP FS313-1110-TAP FS313-1150-TAP
12"	12.00-12.40 12.40-12.80 12.75-13.20 13.10-13.50	6"	2	5/8"	6.8	7-1/2"	2	5/8"	7.1	FS313-1240-TAP FS313-1280-TAP FS313-1320-TAP FS313-1350-TAP

<sup>\*</sup> CC7 tap not available for this size.

♦ One-bolt design

### **OUTLET TAP CODE**

CC (AWWA) THREAD				IP THREAD				
THREAD	Code No.	✓ SUBMITTED ITEM(S)		THREAD	Code No.	✓ SUBMITTED ITEM(S)		
1/2" CC	CC1			1/2" IP	IP1			
3/4" CC	CC3			3/4" IP	IP3			
1" CC	CC4			1" IP	IP4			
1-1/4" CC	CC5			1-1/4" IP	IP5			
1-1/2" CC	CC6			1-1/2" IP	IP6			
2" CC	CC7			2" IP	IP7			

To Order: Select the catalog number for the desired pipe range and complete the catalog number by adding the outlet thread tap code. Example: A single band saddle for 9.05 O.D. pipe with a 3/4" CC thread would be FS313-940-CC3.

#### **FEATURES**

- All components are made of type 304 stainless steel
  All welds are fully passivated for corrosion resistance
  Approved for use on HDPE. If Belleville washers are required, use the prefix FSP313
- Saddles 4" and larger have coined body for gasket retention NBR (Buna-N) rubber pad gasket per ASTM D2000 with raised compression seal
- Rated for working pressure equal to the lesser of pipe pressure rating or 250 psi
- Certified to ANSI/NSF 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



## The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

04/03/20

Sub	mitted	hν

<sup>\*\*</sup> CC6, CC7 and IP7 not available for this size.