

**NIBCO**

1516 Middlebury Street
Elkhart, IN 46516-4740

Phone: 574.295.3000 • **Fax:** 800.234.0557

E-Mail: info@nibco.com • **Web site:** www.nibco.com

Material Number NLG110M, LD-2000 - Butterfly Valve - Ductile Iron, Lug Type, 200 PSI, Gear

The NIBCO® ductile iron lug butterfly valve provides ease of operation with quarter-turn (90 degrees) open to close. With the internal stem/disc geometric drive design, there is no need for pins or bolts that may create leak paths or turbulence in the waterway. An extended neck allows for insulation up to 2 inches. The unique molded-in EPDM seat liner with aluminum bronze disc is recommended for most water applications. Please refer to NIBCO technical data sheets, chemical resistance guides and

[+ more](#)



Specifications

UPC Code	039923718525
Type	Butterfly Valve
Connection Type	L - Lug
Stem Material	Metal - NIBCO - Steel - Stainless
Valve Size	10
Material	DI Ductile Iron
Disc Material	Aluminum Bronze
Valve Operator	Gear Operator
Description	LD20005 10 LUG BFV GEAR OP DUCTILE IRON
*eClass Classification	Ductile Iron Butterfly Valves
All Type of Item	Valve

Turns/Operation

Quarter-Turn

Weight

91.25 lb