


Schedule 40 Fittings Technical
Schedule 40 Fittings Dimensions & Information



Cross


Socket x Mipt x Socket x Mipt



Part Number	Size	G	G1	H	H1	L	L1	M	Approx. Wt. (Lbs.)
421A-010	1	21/32	13/16	1-23/32	1- 7/8	3-7/16	3- 3/4	1- 5/8	.18

Coupling

Socket x Socket



Part Number	Size	L	M	N	Approx. Wt. (Lbs.)
429-003	3/8	2- 5/8	7/8	1/8	.03
429-005	1/2	1-19/32	1- 3/32	3/32	.03
429-005N	1/2	1-5/8	1-1/16	3/32	.02
429-007	3/4	2- 1/8	1- 5/16	3/32	.05
429-007N	3/4	2-1/8	1- 5/16	3/32	.05
429-010	1	2-3/32	1-5/8	3/32	.07
429-010N	1	2-3/32	1-5/8	3/32	.09
429-012	1-1/4	2-11/32	1-31/32	3/32	.10
429-015	1-1/2	2- 5/8	2- 7/32	3/32	.14
429-020	2	2- 7/8	2- 3/4	3/32	.20
429-025	2-1/2	3- 3/4	3- 5/16	3/16	.40
429-030	3	3-31/32	4	3/16	.56
429-040	4	4- 1/4	5- 1/32	3/16	.85
429-045F*	4-1/2	6-1/4	5- 7/16	1-1/4	1.45
429-050	5	6- 3/16	6-1/4	3/16	1.66
429-060	6	6- 5/16	7- 1/4	1/4	2.15
429-080	8	8-11/32	9-11/32	1/4	4.18
429-100	10	10- 3/8	11- 9/16	15/32	7.29
429-100F*	10	12- 3/8	11- 1/2	1- 7/8	8.39
429-120	12	12- 3/8	13-21/32	3/8	11.71
429-120F*	12	14- 3/4	13- 9/16	2- 1/4	13.26
429-140	14	14-13/32	15- 5/8	7/16	27.26
429-140F*	14	16- 1/4	14- 7/8	2- 1/4	17.65
429-160F*	16	18- 5/8	17	2- 5/8	27.00
429-180F*	18	21- 3/4	19- 1/8	3- 3/4	39.45
429-200F*	20	24	21- 3/16	4	52.39
429-240F*	24	29- 1/4	25- 3/8	5- 1/4	82.20

* Fabricated