




45° EII

(Continued)

Socket x Socket




Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
817-045F*	4-1/2	4- 1/2	2	5- 5/8	2.62
817-050	5	4	1-3/8	6-3/8	3.28
817-050F*	5	4- 7/8	1- 7/8	6- 5/16	3.74
817-060	6	4- 3/4	1- 3/4	7-9/16	5.46
817-080	8	6	2	9- 3/4	10.16
817-100	10	7-5/8	2-19/32	12-1/8	18.98
817-100F*	10	8-11/16	3- 7/16	11-15/16	17.37
817-120	12	9-3/16	3-1/8	4-9/32	31.85
817-120F*	12	10- 1/8	3- 7/8	14- 1/8	31.86
817-140	14	10-11/32	3- 5/16	15- 5/8	39.65
817-140F*	14	11- 9/16	4- 9/16	15- 1/2	41.24
817-160F*	16	13- 5/16	5- 5/16	17-11/16	61.48
817-180F*	18	15	6	19- 7/8	87.73
817-200F*	20	16- 3/4	6- 3/4	22- 1/16	112.97
817-240F*	24	20- 3/16	8- 3/16	26- 7/16	208.66

* Fabricated

15° EII

Socket x Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
818-005F*	1/2	1-5/16	5/16	1-1/8	.07
818-007F*	3/4	1-5/16	5/16	1-3/8	.09
818-010F*	1	1-5/8	3/8	1-11/16	.16
818-015F*	1-1/2	2	1/2	2-5/16	.26
818-020F*	2	2- 5/16	9/16	2-13/16	.49
818-025F*	2-1/2	2- 3/4	3/4	3- 7/16	.92
818-030F*	3	3	3/4	4- 1/8	1.14
818-040F*	4	3- 1/8	7/8	5- 3/16	1.89
818-045F*	4-1/2	3- 5/8	1-1/8	5- 5/8	2.36
818-050F*	5	3-15/16	15/16	6- 5/16	2.98
818-060F*	6	4- 3/8	1- 1/8	7- 1/2	4.67
818-080F*	8	4- 1/2	1- 1/4	9- 5/8	9.23