




Schedule 80 CPVC Technical Schedule 80 CPVC Unions

Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar
Dimensions Also Applicable to
8098-XXXCSR EPDM O-Ring Seals




Pressure Rating
1/2" - 4" 235 psi @ 73°F
6" 150 PSI @ 73°F

Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
8058-005CSR	1/2	2	1- 3/16	5/8	1- 7/8	.15
8058-007CSR	3/4	2- 5/32	1- 3/8	21/32	2- 9/32	.22
8058-010CSR	1	2- 9/16	1-11/16	13/16	2- 9/16	.34
8058-012CSR	1-1/4	2-23/32	2- 1/32	13/16	3- 1/8	.46
8058-015CSR	1-1/2	2-27/32	2-13/32	29/32	3-17/32	.62
8058-020CSR	2	3- 7/32	3- 1/32	1- 3/16	4- 7/32	1.02
8058-025CSR	2-1/2	4-3/32	3-9/16	1-15/32	6-5/32	2.51
8058-030CSR	3	4- 3/16	4- 9/32	1- 3/8	6- 5/32	2.58
8058-040CSR	4	4-23/32	5- 1/4	3/4	7-3/4	4.24
8058-060CSR	6	6- 3/16	7-11/16	2-13/16	11- 5/8	12.25

Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal
Dimensions Also Applicable to
897-XXXC EPDM O-Ring Seals



Pressure Rating
235 psi @ 73°F

Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
857-005C	1/2	2- 3/32	1- 9/32	11/32	1-31/32	.15
857-007C	3/4	2- 3/8	1-17/32	11/32	2- 1/2	.28
857-010C	1	2- 9/16	1-27/32	3/8	2- 7/8	.39
857-012C	1-1/4	2- 7/8	2- 7/32	3/8	3- 5/16	.52
857-015C	1-1/2	3- 3/32	2- 9/16	15/32	3- 9/16	.64
857-020C	2	3- 5/8	3- 1/32	9/16	4- 3/16	1.01
857-025C	2-1/2	4- 3/8	3- 5/8	15/16	4- 7/8	1.58
857-030C	3	5	4- 3/8	1- 3/16	5- 3/4	2.50
857-040C	4	5- 7/8	5-13/32	1- 3/8	7- 1/16	3.97