

SIMPLE, EFFECTIVE VALVE BOX DEBRIS PLUGS



Keep dirt, sand, and mud out of valve boxes with compression fit MUD PLUGS

SIZES	Diameters: 5 1/4 to 36-inch. Thickness: 2, 4, or 6-inch
TYPICAL USES	Valve box debris plug
	Temporary non-pressure pipe plugs
ADVANTAGES (Product) ✓ Will not absorb water or dirt	
ADVANTAGES (Floduct)	✓ Will not freeze
	✓ Simple push-in, pull-out installation
	✓ Not prone to cracking or splitting like hard plastics
	✓ Fraction of the cost of the big name product
	✓ Same high quality material used in many life vests
	✓ Flexible, compressible material forms tight seal
	✓ Flexible 350-lb-test non-conductive handle
	✓ Available to fit virtually any box from 5 1/4 to 36-inch diameter
	✓ HardHat Mud Plug offers heavy-duty top with writable surface
	✓ Inexpensive enough to place in all troublesome valve boxes
	▼ Intexpensive enough to place in all troublesome valve boxes
ADVANTAGES (Manufacturer)	✓ Products made in U. S. A. and Infact is an American-owned company
INFACT PRODUCTS ARE AVAILABLE FROM YOUR LOCAL WATERWORKS DISTRIBUTOR	→ BIG inventory; and special orders ship within one week
	✓ No extra charge to drop ship
	→ Minimum order of only one box
WATCH	Supply us with the following information: a) Valve box manufacturer and box model number, or b) Inside diameter of the valve box
OPTIONS A) Havellat Diver	
OPTIONS	1) HardHat Plugs 2) 2-inch thick plugs for shallow valve boxes 3) Tuffer Tags, customized color-coded durable tags



SALES: **(888) 773-9130**FAX: **(615) 206-9787**EMAIL: **info@infactcorp.com**





SIMPLE, EFFECTIVE VALVE BOX DEBRIS PLUGS



Keep dirt, sand, and mud out of valve boxes with compression fit **MUD PLUGS**

STANDARD



HARDHAT (with heavy-duty top layer and writable surface)



Easy push-in, pull-out installation Closed-cell, will not absorb dirt or moisture Plug conforms to sides of valve boxes or pipe Water-proof, flexible, tough foam used in life vests 350-lb-test polypropylene handle — flexible, non-conductive Made in USA

MUD PLUGS BENEFITS

- MATERIAL: Cross-linked, laminated, heat fused, 1.2 or 1.7 density closed cell polyethylene
- ◆ CHARACTERISTICS: Will not absorb water or dirt; bends but will not crack or break
- ◆ STANDARD THICKNESSES: 2-inch, 4-inch, or 6-inch thickness (nominal)
- ♦ STANDARD DIMENSIONS: up to 36 inches in diameter
- ◆ COLOR: 2-inch thickness = white (other colors available in quantity orders)
- ◆ COLOR: 4-inch thickness = light green (other colors available in quantity orders)
- ◆ COLOR: 6-inch thickness = light green (other colors available in quantity orders)
- ◆ FEATURES: Proprietary cutting machine produces no die-cut type concave sides
- ◆ HANDLES: Flexible 350-lb-test polypropylene, 1/2-inch, heat fused polypropylene
- ♦ MADE IN U. S. A.

SAMPLE VALVE BOX PLUG, PIPE PLUG SPECIFICATION: Valve boxes and stored pipe not under pressure shall be protected by using a push-in/pull-out plug manufactured in U. S. A. of 1.2 lb. or 1.7 lb. density closedcell polyethylene material. (The HARDHAT plug will include a top layer of 6.0 lb. density material.) All materials shall be flexible, non-cracking, and will not absorb water. The polyethylene pad shall conform to the sides of the enclosure without the need for any tightening mechanism. The device shall come complete with a 350-lbtest polypropylene handle for easy and secure plug removal and be flexible so as not to interfere with the installation of any enclosure top. The plugs shall be Infact Corporation MUD PLUGS or equal.



SALES: (888) 773-9130 FAX: (615) 206-9787 EMAIL: info@infactcorp.com

