

BALL VALVES | BRASS



Series 7710T Brass Ball Valve

Premium | Full Port
Forged Brass | Italian

Item No.	Size	Connection	Inner	MC
107-401NL	1/4"	FIP x FIP	-	20
107-402NL	3/8"	FIP x FIP	-	20
107-403NL	1/2"	FIP x FIP	-	15
107-404NL	3/4"	FIP x FIP	-	15
107-405NL	1"	FIP x FIP	-	10
107-406NL	1-1/4"	FIP x FIP	-	4
107-407NL	1-1/2"	FIP x FIP	-	4
107-408NL	2"	FIP x FIP	-	2

Features:

- 600PSI/150 WSP
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Double FKM O-ring - maintenance free blowout proof stem design
- PTFE Discs and Seats
- Internal & External anti-friction stem washers
- Corrosion-resistant steel handle
- Made in Italy



Series 7710TC Brass Ball Valve

Premium | Full Port | Nickel
Plated | Forged Brass

Item No.	Desc.	Connection	Inner	MC
107-000NL	1/8"	FIP x FIP	20	200
107-001NL	1/4"	FIP x FIP	20	200
107-002NL	3/8"	FIP x FIP	10	100
107-003NL	1/2"	FIP x FIP	10	100
107-004NL	3/4"	FIP x FIP	10	100
107-005NL	1"	FIP x FIP	10	50
107-006NL	1-1/4"	FIP x FIP	10	20
107-007NL	1-1/2"	FIP x FIP	4	20
107-008NL	2"	FIP x FIP	2	10

Features:

- 600PSI/150 WSP
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Double FKM O-ring - maintenance free blowout proof stem design
- PTFE Discs and Seats
- Internal & External anti-friction stem washers
- Corrosion-resistant steel handle
- Corrosion-resistant Nickel-plated body



Series 7710S Brass Ball Valve

Premium | Full Port
Forged Brass | Italian

Item No.	Size	Connection	Inner	MC
107-453NL	1/2"	SWT x SWT	-	15
107-454NL	3/4"	SWT x SWT	-	15
107-455NL	1"	SWT x SWT	-	10
107-456NL	1-1/4"	SWT x SWT	-	5
107-457NL	1-1/2"	SWT x SWT	-	5
107-458NL	2"	SWT x SWT	-	2

Features:

- 600PSI/150 WSP
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Double FKM O-ring - maintenance free blowout proof stem design
- PTFE Discs and Seats
- Internal & External anti-friction stem washers
- Corrosion-resistant steel handle
- Made in Italy



Series 7700T Brass Ball Valve

Premium | Full Port
Brass | Packing Gland

Item No.	Desc.	Connection	Inner	MC
107-821NL	1/4"	FIP x FIP	15	120
107-822NL	3/8"	FIP x FIP	15	120
107-823NL	1/2"	FIP x FIP	-	20
107-824NL	3/4"	FIP x FIP	-	15
107-825NL	1"	FIP x FIP	-	10
107-826NL	1-1/4"	FIP x FIP	4	24
107-827NL	1-1/2"	FIP x FIP	2	24
107-828NL	2"	FIP x FIP	2	12
107-829NL	2-1/2"	FIP x FIP	2	6
107-830NL	3"	FIP x FIP	2	4
107-831NL	4"	FIP x FIP	-	2

Features:

- 600PSI/150 WSP (1/2"-2")
- 400PSI Non-Shock WOG (2-1/2" - 4")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle with vinyl grip

