**Submitted Model No.: Specific Features:** 

### 86200▲ 86201▲ 5 5/16" (135 mm) 5" (128 mm) 6 1/8" (256 mm) 10 15/32" (266 mm) ٧ 11 5/8" (295 mm) (76 mm) 6" (152 mm) 60"-82" 4 mm (1524 mm-2083 mm) 60"-82" (1524 mm-2083 mm) 86275▲ 86280▲ 5 1/4" (133 mm) (128 mm) 9 7/16" (239 mm) 11 5/16' 2 15/16" (74 mm) (288 mm) 5 29/32" (150 mm) 5 9/16" (142 mm) 60"-82" 60"-82" (1524 mm-2083 mm) (1524 mm-2083 mm)

### ▲ Designate proper finish suffix

### Spray Patterns



Spray









H<sub>2</sub>0kinetic® Spray w/ Massage

# BRIZO

## **HYDRATI**® 2 1 SHOWER

- 211 Shower
- Push Button Selection

### **FEATURES:**

- H<sub>2</sub>Okinetic® Technology
- MagnaDock® Technology

### **STANDARD SPECIFICATIONS:**

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min) @ 550 kPa
- Showerhead and handshower all in one
- 3-way diverter showerhead only, handshower only, and combo
- Integrated handshower docks securely into showerhead with MagneDock<sup>®</sup> technology
- Four -setting push button handshower
- 60" (1524 mm) stretchable finished metal hose stretches to 82" (2083 mm) for extra reach
- For use with automatic compensating valves rated at 1.5 gpm (5.7 L/min) or less

### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

#### **COMPLIES WITH:**

■ ASME A112.18.1 / CSA B125.1 ◆ Loc (ANS) A117.1 ICC/ANSI A117.1

Brizo Kitchen & Bath Company

Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, nonserviceable parts of the wand assembly.